GREEN AUDIT REPORT



2021-22

Submitted to Smt. Chandibai Himathmal Mansukhani college

Ulhasnagar, Mumbai - 421003

Prepared by Roshni Udyavar & Associates

Wadala East, Mumbai



Green Audit Team

- **Dr. Roshni U. Yehuda** Team leader B.Arch., M.Arch., Ph.D. (Resource Management)
- **Ar. Trupti Kamat** Project Co-ordinator B.Arch., M.Arch., IGBC AP, GEM CP.
- Mr. S. Kale BEE-certified Energy Auditor B.E. (Electrical)
- Mr. Mahesh Harad- Audit Assistant Senior Engineer (B.E. Electrical)
- **Mr. Navneet Kale** Audit Assistant B.E. (Electrical)

Preface

A Green Audit is the first step to reducing a **building's water, waste, energy and carbon footprint and environmental impact**. The analysis of consumption of water and energy as well as generation of waste is used to provide recommendations on solutions such as rainwater harvesting, water and waste management, energy management including the addition of renewable energy. *The objective of the green audit is to transform to be self-reliant and self-sustainable in water and energy and create a zero-waste campus*.

In the long run, such a building will have greatly reduced its operating costs, carbon footprint and impact on the city's infrastructure. Upcoming and future regulations for buildings will require to follow green norms and energy-efficient measures including the Energy Conservation Building Code (ECBC). Hence, Green Audits will help buildings to achieve the norms.

The methodology of the Green Audit involves evaluation of the **water**, **energy and waste** consumption in the building or premises through online surveys, walk-throughs and detailed audits (where required). The results are analysed against existing Indian and international benchmarks and standards.

An **Environmental Management Plan** is prepared as an outcome of the audit based on a detailed analysis of data collected. This has the potential to reduce the consumption of resources through the use of appropriate technologies, design and planning without affecting the process or quality of an Institute's functioning. The investment and payback calculations are provided such that the plan can be implemented in whole or phases as desired.

The benefits of conducting a green audit are a better understanding of the building systems, along with recommendations for improvement with a goal of self-reliance on resources and reducing the load on public infrastructure.

Through the audit report, we endeavour to provide cost-effective and long-term solutions in a continuous process of conservation of resources. The data collected for a month has been presented through appropriate visual representations for easy

understanding of the technical information. Glossary, abbreviations, units of measurements and references are provided for those who are further interested. Any suggestions or edits in the report are welcome and can be sent to roshniudyavar@gmail.com

This Green Audit Report is meant for academic and research purposes only. For legal issues, a separate study is required, and hence the results of this report cannot be used as evidence for any legal case within India or abroad.

Acknowledgement

We extend our sincere thanks to Hyderabad (Sind) National Collegiate Board, the Management of Smt. Chandibai Himathmal Mansukhani College for taking up the initiative to conduct Green Audit.

We are grateful to the Principal of the College, Dr Manju Lalwani Pathak for her support and enthusiasm in taking up this venture. We acknowledge the initiative of the college Internal Quality Assurance Cell (IQAC) for providing us with detailed information needed to conduct the audit and their presence during the audit visits.

We would also like to thank the support staff for their help as and when required during the audit visits.

Green Audit Team

Roshni Udyavar & Associates

Abbreviations

- **BEE** Bureau of Energy Efficiency
- **BLDC** Brushless Direct Current
- **BUA -** Built-up area
- **CFL** Compact Fluorescent Lamps
- CMH Cubic Meters Per Hour
- **DBT** Dry Bulb Temperature
- **DEF** Daylight extent factor
- **DG** Diesel Generator
- **EER** Energy efficiency ratio
- **ECBC** Energy Conservation Building Code
- **ECMs** Energy Conservation Measures
- **EPI** Energy Performance Index
- **FTLs** Fluorescent Tube Lights
- **HT** High Tension
- **HVAC** Heating, ventilation, and air conditioning
- **LED** Light Emitting Diodes
- **LPD** Lighting Power Density
- **LPG** Liquefied petroleum gas
- MNRE Ministry of New and Renewable Energy
- MRT Mean Radiant Temperature
- NAAC The National Assessment and Accreditation Council
- NBC National Building Code
- NCEF National Clean Energy Fund
- **PPA** Power Purchase Agreement

- RA CHARGE Regulatory Asset Charge
- **RPM** Revolutions Per Minute
- **RH** Relative Humidity
- **SEC** Specific Energy Consumption
- **SECI -** Solar Energy Corporation of India
- **Solar PV -** Solar Photovoltaic
- **TOD** Time of Day
- **TR** Tons of refrigeration
- **WBT** Wet Bulb Temperature
- **WWR** Window to Wall Ratio

Units of Measurements

- C- Celsius
- cm Centimetre
- Ft Foot
- H Hour
- **kW** Kilowatt of electricity
- **kWh** kilowatt-hour
- kWh/m²/year- kilowatt per square meter per year
- **kVA** kilovolt-ampere
- lm Lumens
- lm/W Lumens per Watt
- **lux** a unit of Illuminance
- m Meter
- mm Millimetre
- W Watt
- W/m² Watts per square meter
- Wh Watthour

Table of Contents

| Green Au | lit Team | 2 |
|-------------|--|----|
| Preface | | 3 |
| Acknowle | dgement | 5 |
| Abbreviat | ions | 6 |
| Units of M | easurements | 8 |
| List of Tal | oles | 12 |
| List of Fig | ures | 14 |
| | tes | |
| | Summary 2021-22 | |
| | duction | |
| | ojectives of the Green Audit | |
| | cope of Work | |
| | nderstanding of the Audited Area | |
| | Methodology | |
| | ata Collection | |
| | ata Analysis | |
| | sis and Benchmarking | |
| | nergy | |
| 3.1.1 | Overall Energy Consumption | |
| 3.1.2 | Lighting Energy Consumption | 34 |
| 3.1.3 | Energy Consumption for Thermal Comfort | 41 |
| 3.1.4 | Equipment Energy Consumption | 45 |
| 3.1.5 | Electrical system study and leakage currents | 48 |
| 3.1.6 | Benchmarking - Energy Performance Index (EPI) | 54 |
| 3.1.7 | Benchmarking - Specific Energy Consumption (SEC) | 55 |
| 3.1.8 | Billing Analysis and Metering system | 55 |
| 3.2 W | ater | 56 |

| | 3.2.1. Rain Water Harvesting | 60 |
|-----|--|------|
| 3. | .3 Solid Waste | 60 |
| 3. | .4 Environment Quality | 61 |
| ŀ. | Recommendations for Green Campus and Feasibility for Smt. Chand | ibai |
| Him | nathmal Mansukhani college | 63 |
| 4. | .1 Visual Comfort and Energy Efficiency | 63 |
| 4. | .2 Thermal Comfort and Energy Efficiency | 65 |
| | 4.2.1 Replacement of regular fans with BEE star-rated fans and Brushless Direct Current (Efans | |
| | 4.2.2 AC maintenance | 65 |
| 4. | .3 Recommendations for Solar PV system | 66 |
| 4. | .4 General Recommendations and best practices for energy conservation | 67 |
| 4. | .5 Recommendations for Electrical system and Earthing | 68 |
| 4. | .6. Energy Bills | 70 |
| | 4.6.1. Change of Tariff | 70 |
| | 4.6.2. Installation of APFC panel | 70 |
| 4. | .7 Retrofit of Water Efficient Equipment | 71 |
| 4. | .8 Waste Segregation and Composting | 72 |
| 4. | .9 Indoor Air Quality | 72 |
| 4. | .10 Environment Improvement | 73 |
| 4. | .11 Green Rating | 74 |
| 5. | Glossary | 75 |
| ó. | References | 79 |
| 7. | Annexure | 80 |
| A. | Usage data collection template | 80 |
| В. | | |
| C. | | |
| D. | | |
| E. | | |
| F. | • | |

| G. | Energy benchmarks for Commercial Buildings | 95 |
|----|---|-----|
| Н. | List of Vendors | 96 |
| I. | Unitary AC Operation, Inspection and Maintenance Guidelines | 97 |
| J. | Energy Auditor's Certificate | 101 |
| K. | BEE Master Trainer Certificate | 102 |
| L. | BEE Empaneled Expert professional | 103 |
| M. | Renewable Energy Mashav Course Certificate | 104 |

List of Tables

| Table 1: Key Recommendations for improving the environment at Smt. Char | ıdibai |
|--|--------|
| Himathmal Mansukhani college | 18 |
| Table 2: Floor-wise facility distribution in the college | 22 |
| Table 3: Steps in the Green Audit | 26 |
| Table 4: Instruments used for the study | 30 |
| Table 5: Schedule of data collection based on actual visits | 30 |
| Table 6: Break- up of the total population of college | 31 |
| Table 7: Number and kWh distribution of all Lights | 34 |
| Table 8: Total floor-wise annual Lighting Consumption (kWh) | 35 |
| Table 9: LPD for some important activity areas using the 'Space Function Method' | 36 |
| Table 10: Comparative efficacies and environmental impacts of lamps | 36 |
| Table 11: Summary of lux levels comparison with NBC | 40 |
| Table 12: Total floor-wise annual energy consumption by Fans (kWh/year) | 42 |
| Table 13: Total floor-wise AC consumption (kWh/year) | 42 |
| Table 14: Details of audited AC units with their Performance parameters | 43 |
| Table 15: Energy efficiency ratio as specified by BEE for split AC | 44 |
| Table 16: Type of Equipment and their annual usage | 46 |
| Table 17: Total floor-wise Equipment consumption (kWh/year) | 46 |
| Table 18: Detail of the pumps | 47 |
| Table 19: Study of main supply cables | 48 |
| Table 20: Results of thermal imaging of distribution panels | 49 |
| Table 21:Earth Resistance measurement | 51 |
| Table 22: Observations with actual images | 54 |
| Table 23: EPI benchmark by BEE for Institutes | 54 |
| Table 24: Tariff Structure as per the Mahadiscom for Year 2022 | 55 |
| Table 25: Total water usage of the Campus | 57 |
| Table 26: Details of faucets, flushing devices and water coolers in the College | 60 |
| Table 27: Table for calculation of Replacement of tube lights and LED lights | 63 |
| Table 20. Energy officiency improvement massures | 61 |

| Table 29: Replacement of Regular fans with BEE star rated/ Brushless | Direct Current |
|--|----------------|
| (BLDC) fans | 65 |
| Table 30: Solar Rooftop plant calculation | 66 |
| Table 31: Issues in electrical system w.r.t to their risk category and recom | mendation69 |
| Table 32: Retrofit for Water Efficient Equipment | 71 |
| Table 33: Green Building Rating Systems | 74 |

List of Figures

| Figure 1: Methodology of the Green Audit at Smt. Chandibai Himathmal Mansukhani |
|--|
| college27 |
| Figure 2: Distribution of Annual Energy Consumption based on end use32 |
| Figure 3: Distribution of Annual Energy Consumption as per Connected Load32 |
| Figure 4 : Distribution of Annual Energy Consumption Floor-wise33 |
| Figure 5: Types of lights and their consumption in percentage34 |
| Figure 6: Percentage breakup of Floor-wise Annual Energy Consumption of Lights35 |
| Figure 7: Percentage of areas complying with LPD norms as per ECBC using Space |
| Function Method36 |
| Figure 8: Conditioned and un-conditioned areas in Smt. Chandibai Himathmal |
| Mansukhani college41 |
| Figure 9: Percentage breakup of Floor-wise Annual Energy Consumption of Fans41 |
| Figure 10: Percentage breakup of Floor-wise Annual Energy Consumption of AC42 |
| Figure 11: Types of equipment45 |
| Figure 12: Percentage breakup of Floor-wise Annual Energy Consumption of Equipment |
| 46 |
| Figure 13: Monthly billed units by meter56 |
| Figure 14: Time Switches64 |
| Figure 15: Campus Layout83 |

List of Plates

| Plate 1: Classroom in extension building | 22 |
|--|-----------|
| Plate 2: Classroom 315 in the main building | 22 |
| Plate 3: Library on the ground floor of Main Building | 23 |
| Plate 4: Third floor and First-floor corridor- Main Building | 23 |
| Plate 5: Chemistry lab | 23 |
| Plate 6: Butterfly Garden | 24 |
| Plate 7:Borewell no 2 | 24 |
| Plate 8 : Ramp for universal access | 24 |
| Plate 9: Solar panel for lighting of Pump room | 24 |
| Plate 10 : Passage of Extension Building | 24 |
| Plate 11: Terrace above the third floor(main building) | 25 |
| Plate 12: Main entrance (East Side) | 25 |
| Plate 13: Biology lab- Incubators | 47 |
| Plate 14: Computer lab | 47 |
| Plate 15:Auditorium having projectors | 47 |
| Plate 16: Incinerator located in ladies toilet | 60 |
| Plate 17: Bins for segregation of waste at source | 60 |
| Plate 18 :QR coding of the trees on campus | 61 |
| Plate 19 :Butterfly Garden | 61 |
| Plate 20 : Vegetation in front of main building | 61 |
| Plate 21: Botanical garden | 61 |
| Plate 22: Oreintal Magpie-Robin | 62 |
| Plate 23: White throated Kingfisher | 62 |
| Plate 24: Coppersmith Barbet | |
| Plate 25: Rose Ringed Parakeet | 62 |
| Plate 26: Existing 36W Fluorescent Tube Lights | 63 |
| Plate 27: Proposed 18W LED Tube Lights of 1800 Lumens output (efficacy = | 100 L/ W) |
| | |
| Plate 28: Existing Ceiling Fan of 60 W | 65 |
| Plate 29: Proposed Ceiling Fan of Atomberg Gorilla 32W | |
| Plate 30. Picture showing the proposed Solar PV panels | 66 |

| Plate 31: Existing Single Flush | 71 |
|--|--------|
| Plate 32: Proposed Dual Flush | 71 |
| Plate 33: Proposed water-saving aerators for the wash basin faucets | 71 |
| Plate 34: Indoor plants - Dieffenbachia amoena, Chlorophytum comosum and E | pimnun |
| auries | 72 |
| Plate 35: Plant species attracting birds and butterflies | 73 |

Executive Summary 2021-22

The Smt. Chandibai Himathmal Mansukhani college premises has an energy consumption of **95,498 kWh** for the academic year 2021-22 as per metered electricity bill. This may not be the total consumption during full occupancy as the college functioned offline for only 3 months in 2021-22 due to the Covid-19 Pandemic. The main areas of electricity consumption are Lighting, Fans, Air Conditioning and Equipment. Of this, **Equipment** load is the **highest at 29% (31,599 kWh)** followed by **Lighting load at 27% (29,380 kWh)**, **AC at 22% (23,826 kWh)**, and **Fans at 22% (24,067 kWh)**. **Seven percent** of the College space is **air-conditioned** which includes IT labs, an auditorium and a few administrative spaces, having only split ACs. The college functions in two buildings, the Main building(G+4) and the Extension building(G+3).

The Energy Performance Index (EPI) of the building is 7.86 kWh/sq. m/ year which is well below the Bureau of Energy Efficiency (BEE), Govt. of India's national benchmark of 150 kWh/sq. m/ year for institutional buildings in warm-humid climate. The BEE's benchmark for nearly zero energy buildings is 15.00 kWh/sq. m/ year which is currently achieved by the college. The college has scope for adding solar panels on its roof top.

86 % of spaces within the college comply with the maximum allowable Lighting Power Density (LPD) as per the **Space Function method of ECBC 2017**. Also, the lighting levels meet the National Building Code (NBC) standard in most of the spaces.

According to municipal water bills, the average monthly consumption is around **427 KL** which comes to about **20 KL** per day which is around **9.4%** of the standards prescribed by the NBC for domestic usage. The flushing requirement of the college is fulfilled by the bore well present on site. There is scope for reducing water consumption to around 50% by using aerators for taps, and drip irrigation for watering trees.

The college generates Paper, Glass, Cardboard, Electrical and Electronic waste which constitutes of **50% of recyclable solid waste**, while **50% of organic** waste is generated by food waste from the canteen and leaf litter is composted on site. The electronic waste generated of 350 kg was collected by the Eco Friend industries, for the audited period.

The college has good ambient air quality due to the vegetation on campus. The main building is renovated recently, and all windows have white PVC frames. Classrooms, corridors and staircases are large and spacious with good light, ventilation and signages.

A summary of the key recommendations from the green audit is provided in Table 1 here along with savings, cost and a simple payback period.

| Recommended Measure | Potential Savings per year (kWh/ Litres) | Potential Financial Savings Per year (Rs) | Estimated Investment (Rs) | Simple Pay Back Period (year) |
|---|--|---|---------------------------------|--|
| | Energy | | | |
| Replacement of T8 (40W) Fluorescent Tube Lights (FTLs) along with electromagnetic ballast with 18W LED Tube Lights having lumen output of 1800 (efficacy = 100 Lumens per Watt) | 3,105 | 57,374 | 45,540 | 1 |
| Replacement of regular fans with BEE star rated fans and Brushless Direct Current (BLDC) fans | 9,536 | 1,76,226 | 20,79,000 | 11.8 |
| Installation of APFC panel | 0 | 96,000 | 1,50,000 | 1.5 |
| Renewable Energy | | | | |
| Installation of solar PV and Net metering to be arranged with Utility - Mahadiscom | 57,450 | 10,61,676 | 14,64,439 | 1.4 |
| Total | 70,091 | 13,91,276 | 37,38,979 | 3 |
| Water | | | | |
| Wash basin faucet to water saving aerators | 50% | NA | | NA |
| Water meter to measure borewell water usage | Mandato | ry | 500 | NA |

Table 1: Key Recommendations for improving the environment at Smt. Chandibai Himathmal

Mansukhani college

BEE-Bureau of Energy Efficiency

kWh- Kilowatt hour

1. Introduction

Smt. Chandibai Himathmal Mansukhani college was established in 1965 and managed by Hyderabad (Sind) National Collegiate Board (HSNC board). Smt. Chandibai Himathmal Mansukhani College is one of the largest Colleges at the University of Mumbai located in an area of 16 acres (65,000 m2) of lush green land. The campus is rich in scenic and greenery around. The college has taken extra measures to protect and conserve its natural environment and the greenery.

The College was established with about 250 students and four departments and has transformed into one of the largest Colleges affiliated with the University of Mumbai. The college has more than 10,000 students and 400+ teaching and non-teaching staff. There are 27 Undergraduate and 11 Postgraduate Departments, 06 Research Centres, 08 Professional and 11 Certificate Courses and 02 prestigious UGC sponsored community outreach centres.

The College won second prize at the Intercollegiate "Green and Clean Environment Campus" organized by the Indian Merchants Chamber in 2011-2012. The college has one of the largest NSS Units of the University of Mumbai with an enrolment of 300 Volunteers per year taking major initiatives in organizing the Social and Community based programmes in the City of Ulhasnagar and Districts of Mumbai and Thane.

1.1 Objectives of the Green Audit

The objective of the green audit are as follows

- Quantify energy, water and waste consumption;
- Identify energy saving opportunities resulting in lowered energy bills, less use of fossil fuel-based energy and lower carbon footprint;
- Identify wastages in use and devise solutions such as smart/automated equipment to reduce consumption;
- Introduction of renewable energy to reduce operational energy cost (if required)
- Introducing measures to reduce water consumption and optimise rainwater harvesting potentials.
- Suggesting measures to waste management.

1.2 Scope of Work

Energy:

- Overview of existing facilities and electric appliances (lights, fans, heater, air conditioner etc.), operating systems like electrical distribution system, metering system, tariff, electricity and Power consumption etc. by use of appropriate instrumentation.
- Establishing a baseline of energy consumption and identify major causes of low operating efficiency and recommended improvements / better operating practices.
- Summary of findings and recommendations and energy conservation measures.
- Assessment of Building Envelope energy efficiency and possible retrofit solutions
- Estimation of the costs associated with the implementation of each of the proposed energy conservation measures (ECMs).
- Quantifying the extent of energy savings/performance improvement that can be
 achieved by upgrading and/or replacing the existing electrical appliance with the
 best efficiency electrical appliance available in the market and other energy
 efficiency/conservation measures based on the analysis of the measurements.
- Scope of renewable energy applications

Water:

- Data collection on water usage, storage capacity, daily consumption patterns, infrastructure and equipment.
- Data analysis to provide the scope of improvement in water usage.
- Solutions for rainwater harvesting storage or ground water recharge
- Possibility of waste water (black or grey water recycling)

Solid Waste:

- Survey of waste on the premises categorization and quantification
- Analysis and research on possible methods of waste disposal and treatment (of organic waste)
- Solutions for recycling E-waste and recyclables

Environmental Quality:

- Assessment of IEQ Visual, Thermal and Acoustic comfort, IAQ (Ventilation)
- Survey of noise and vegetation in the premises levels and extent
- Analysis and possible solutions to reduce the noise levels and enhance the greenery and biodiversity within the campus

1.3 Understanding of the Audited Area

The total built-up area of **1,30,825 sq. ft. (12,154 sq. m)**, is considered for the audit and was evaluated based on existing drawings, information as well as on-site measurements as it forms the basis of assessment of the energy, water and waste consumption to existing benchmarks. The college campus has an area of **64,749 sq m**, which has other colleges like law, engineering, pharmacy.

The college functions mainly in 2 main buildings namely the Main building and Extension building. Main building has Ground to fourth floors while extension building has ground to $3^{\rm rd}$ floor.

Categorization of the spaces as administrative spaces (offices, staff rooms, etc.), common spaces (Toilets, storage, canteen, library, etc.), circulation spaces (staircase, corridors) and conditioned vs. non-conditioned spaces (computer labs and classrooms) was then carried out.

The analysis shows that **14%** of the total built-up area of the college is used as a common passage. The college building has classrooms for Junior and Senior Degree college, computer labs, administrative offices, staff rooms, conference rooms, auditorium, library, common passages, staircase, lift etc.

The description of facilities and activities on each floor are given in Table 2:

| S. No. | Floor | Name of the Facility | |
|--------|--------------|---|--|
| 1 | Ground Floor | Library in both buildings, Canteen, Auditorium, | |
| | | Toilets, Chemistry lab, Professor's common room, NSS | |
| | | and NCC rooms, Gymkhana, Examination Cell. | |
| 2 | First Floor | Administrative office, Principal's cabin, HoD cabins, | |
| | | Girls common room, Classrooms, Laboratories, Water | |

| | | | room, Toilets |
|---|---|--------------|--|
| | 3 | Second Floor | HoD cabins, Classrooms, Water room, Laboratories |
| Γ | 4 | Third Floor | Classroom, HoD cabins, Water room, Toilets |
| | 5 | Fourth Floor | Store rooms, Class rooms |

Table 2: Floor-wise facility distribution in the college

Some sample photographs taken during the audit showing different spaces and equipment are provided in the following pages.



Plate 1: Classroom in extension building



Plate 2: Classroom 315 in the main building





Plate 3: Library on the ground floor of Main Building





Plate 4: Third floor and First-floor corridor- Main Building



Plate 5: Chemistry lab



Plate 6: Butterfly Garden



Plate 7:Borewell no 2



Plate 9: Solar panel for lighting of Pump room



Plate 8 : Ramp for universal access



Plate 10: Passage of Extension Building



Plate 11: Terrace above the third floor(main building)



Plate 12: Main entrance (East Side)

2. Audit Methodology

Five steps involved in the audit process are as follows:

| Step | Objective | Activities |
|--------|--|---|
| Step 1 | Audit of historical data | Online data collectionBuilding drawings, utility bills |
| Step 2 | Screening survey or walk-through audit | A random verification of inventory of all electrical and electro-mechanical devices including lights, fans, motors, pumps, ACs, water equipment, Inspection of the site for water, waste and environmental information |
| Step 3 | On-site investigations | Verification of online data submitted through ground survey and observations Measurement of various equipment efficiencies, specific power consumption (SPC) kW/TR of equipment w.r.t. manufacturer's data. Monitoring of actual energy consumption of AC and other electrical loads Observe operation of equipment and evaluate their performance w.r.t. manufacturer's data Conduct random lighting audit of habitable spaces and compare with National Building Code (NBC) 2016 standards. Study of air conditioning loads and performance Study of power system and performance Study of illumination system – LUX levels, Lighting Power Density (LPD) Inspection of water, waste and environmental issues including flooding, stormwater system |
| Step 4 | Data Analysis | Analysis of all criteria and comparison with standards and benchmarks Recommendations |
| Step 5 | Documentation and Report | Preparation of detailed report with documentation, calculation and all technical information, summary and recommendations |

Table 3: Steps in the Green Audit

A diagrammatic representation of the methodology is provided in the flow chart below:




Figure 1: Methodology of the Green Audit at Smt. Chandibai Himathmal Mansukhani college

2.1 Data Collection

General Data collection such as the year of establishment of the college, number of

students and staff, inclusion and exclusion of spaces and equipment for the audit were

obtained through one-to-one interviews and discussions with key informants who also

assisted in the collection of building drawings and electricity bills for the past 1 years

(June 2021to May 2022).

Walk-through Audit

A walk-through audit was conducted by the Team which was followed by a few more

visits to review the accuracy of the data. Special guided visits of the campus were

conducted along with Dr. Rashmi Deshpande.

Detailed Audit and Measurements

A detailed audit of the air conditioning system (window and spit units), as well as the

electrical system, was conducted by our BEE-certified energy auditor team. The indoor

and outdoor units of the Air Conditioners were tested for refrigerant flow and pressure,

refrigerant temperature, actual energy consumption and cooling capacity. These are

elaborated in section 3.1.3 and compared with standards in the analysis section.

The energy audit study was carried out for the year, during the lockdown period, and

hence the building had limited occupancy and load on the systems, as only

administrative staff was present in the college. For the audit purpose, some of the air-

conditioning systems were switched ON to generate load on the system. Below are

some pictures of the detailed audit in process.

The observation Checklist was used during the walk-through audits to gather

information about the location of windows, Window Wall Ratio (WWR), number and

type of lights, fans, air conditioners and Equipment

BEE: Bureau of Energy Efficiency

28

Instruments Used

For the energy audit, the following instruments were used:

| Instrument | Name |
|-------------|--|
| A GOO - | Clamp-on type Power/Energy meter |
| | Clamp On Earth Tester Meggar Make. |
| | Thermal Imager Fluke Make Tis-10 Series. |
| ANEMIOMETER | Anemometers – to measure the velocity of gases Luthron Make. |
| | Digital Thermometers for liquid /surface temperature. |



Lux meter Luthron Make.

Table 4: Instruments used for the study

Measurement of Illuminance

Lux levels were measured at 40 different spaces by using a Lux Meter over a grid of 9 points measured at working plane height with artificial light between 1100 to 1700 hours. The average reading was then compared with the mid-point reading of the recommended levels in the National Building Code, 2016.

Schedule of Data Collection

| S. No. | Audit Activity | College and Green Audit Team | Date |
|-----------|---|--|---------------------------------|
| 1. | Preliminary visit and walk-through audit | Dr. Roshni Yehuda, Director, Roshni Udyavar & Associates Dr. Rashmi Deshpande, Assistant Professor, CHM College | 04.04.2022 |
| 2. | Online data form link provided to college | Dr. Manju Lalwani Pathak, Principal, CHM College | 05.04.2022 |
| 3. | Online data submission | Dr. Rashmi Deshpande, Assistant Professor, CHM College | 17.06.2022 |
| 4. | Walk through and detailed audit Ar. Trupti Kamat, Project Coordinator, Roshni Udyavar & Associates Dr. Rashmi Deshpande, Assistant Professor, CHM College | | 25.06.2022 |
| 5. | Detailed audit of air conditioning, meters and power systems | Mr. Navneet Kale and Mr. Mahesh Harad, Energy Audit Assistants, Roshni Udyavar & Associates | 07.07.2022 and 08.07.2022 |

Table 5: Schedule of data collection based on actual visits

2.2 Data Analysis

The collected data was analysed and visually represented using pie charts, bar graphs, and tabulations in each of the audit areas. They were assessed against existing benchmarks and standards such as Energy Performance Index (EPI), Lighting Power Density (LPD) as per Energy Conservation Building Code (ECBC) 2007, appropriate illuminance levels (Lux) for visual comfort, and Specific Energy Consumption (SEC) as specified by National Building Code 2016, Window Wall Ratio (WWR) and several others.

Calculation of Wattage

The wattage of lights, fans, AC and equipment were made based on data submitted online by the college and were verified through a random survey during an on-site investigation. The complete consolidated data is provided in Annexure A.

Information on Population and Area for Energy Performance Index (EPI) and Specific Energy Consumption (SEC)

Information on the number of people using a specific space was obtained from the online questionnaire and interpolated to obtain occupancy for fresh air calculations. For area calculations, the total built-up area provided in an online questionnaire and building drawings were utilized. As per online data submitted, the approximate total population of the college is **11326 people**. This will be used for SEC calculation. The total built-up area of the college considered for EPI is **1,30,825 sq. ft. (12,154 sq. m)**.

| Sr no. | Category | No. of Person | |
|--------|----------------------|---------------|--|
| 1 | Students | 10975 | |
| 2 | Teachers | 171 | |
| 3 | Non-Teaching Staff | 173 | |
| 4 | Administrative Staff | 7 | |
| Total | | 11326 | |

Table 6: Break- up of the total population of college

3. Analysis and Benchmarking

3.1 Energy

3.1.1 Overall Energy Consumption

The overall electricity load at CHM college can be divided into four major sections viz. Lights, Fans, Air conditioners and Equipment. The total **conditioned area in the college is 7%** while the overall AC load corresponding to this conditioned area is 22%. The college has a few office areas, a conference room, a principal room, and computer labs which are fully air-conditioned and have a significant number of computers and lights. The break-up of energy consumption among the four major contributors enduse-wise, connected load and as per floor-wise is shown in Figure 2, Figure 3, and Figure 4 respectively.




Figure 2: Distribution of Annual Energy Consumption based on end use




Figure 3: Distribution of Annual Energy Consumption as per Connected Load




Figure 4: Distribution of Annual Energy Consumption Floor-wise

Summary of observations – overall energy consumption:

- 1. The total calculated annual energy consumption of the campus is **1,08,872 kWh**.
- 2. The total billed electricity for the college for June 2021 to May 2022 is **95,498 kWh**.
- **3.** The diversity factor is **1.14**. This may be due to occupancy information provided by the college considering full occupancy.
- 4. The contribution of **Equipment is 31,599 kWh (29%)**, **AC is 23,826 kWh (22%)**, **Lights is 29,380 kWh (27%)**, and **Fans is 24,067 kWh (22%)**
- 5. As per the total connected load, the contribution of **Equipment is 39%, AC is 28%, Lights is 18% and Fan is 15%.**
- 6. The total air-conditioned area in the college is 7% while the overall AC load corresponding to this conditioned area is 22%
- 7. The floor-wise consumption shows that the second, first and ground floors have the majority consumption as compared to all other floors. This is mainly due to the energy consumption of equipment used in labs and administrative spaces mainly located on the first and second floor while the Ground floor houses spaces like library and chemistry labs in main building, while an auditorium in an extension building
- 8. The College has an office area, conference room, principal room, and computer labs which are fully air-conditioned and have a significant number of computers and lights.

9. **Circulation spaces** i.e. corridors and staircases, attribute to around **14% of the built area while consuming minimal energy**. Circulation spaces are also naturally lit and ventilated with a parapet wall.

3.1.2 Lighting Energy Consumption

3.1.2.1 Artificial lighting

Artificial lighting contributes to **27% (29,380kWh) of the total consumption** in CHM college. Classrooms and other habitable spaces have overall good day litght while some areas have indirect day lighting through corridors. College has installed Philips PureLine Slim 50mm luminaries (efficacy of 100 lm/W) which provide good diffuse light (reducing shadow) for library. As college is going through major renovation, majority of the lamps are replaced with LED Tubelights and LED ceiling recessed lights. Hence campus has 90% LED lights as shown in Fig. 5. 84% of the lighting energy consumption is from LED. The types and wattage of lamps used are shown in figure 5 and Table 7.




Figure 5: Types of lights and their consumption in percentage

| S. No. | Lamp Type | Approximate wattage per lamp (W) | Numbers | Total Consumption (kWh) |
|-------------|-----------------|----------------------------------|----------|----------------------------|
| 1. | LED Bulb | 15 | 175 | 1963.6 |
| 2. | LED Tube Lights | 36 | 1010 | 22759.86 |
| 3 | Tubelight | 54 | 132 | 4656.96 |
| Grand total | | 1317 | 29380.42 | |

Table 7: Number and kWh distribution of all Lights




Figure 6: Percentage breakup of Floor-wise Annual Energy Consumption of Lights

| Sr no | Floor | Sum of Total usage kWh/year | | | |
|-------|--------------|-----------------------------|--|--|--|
| 1 | Ground floor | 8554.83 | | | |
| 2 | 1st Floor | 7909.6 | | | |
| 3 | 2nd Floor | 5554.72 | | | |
| 4 | 3rd Floor | 6366 | | | |
| 5 | 4th Floor | 995.52 | | | |
| | Grand Total | 29380.43 | | | |

Table 8: Total floor-wise annual Lighting Consumption (kWh)

3.1.2.2 Lighting Power Density (LPD)

The Energy Conservation Building Code 2017 defines Lighting Power Density (LPD) as the maximum lighting power per unit area of space as per its function or building as per its classification.

LPD is a benchmark for the maximum allowable light per unit area provided in the ECBC 2017 and has been used here to compare with the lighting power allowance of each area in the college. The LPD using the 'Space Function Method' for some important activity areas has been calculated and compared with ECBC 2017 in Table 9. It is observed that 86% of the spaces in the college comply with LPD norms provided in ECBC.

| S. No. | Space | LPD as per ECBC | Calculated LPD | Meeting with |
|--------|-------------------------|-----------------|----------------|---------------|
| | | 2017 (W/sq. m) | (W/sq. m) | ECBC Standard |
| 1. | Library – reading Area | 10.00 | 30 | No |
| 2. | Classroom | 13.8 | 4.27 | Yes |
| 3. | Lab- Physics, Chemistry | 15.1 | 18.62 | No |
| 4. | Computer lab | 15.1 | 6.52 | Yes |

Table 9: LPD for some important activity areas using the 'Space Function Method'




Figure 7: Percentage of areas complying with LPD norms as per ECBC using Space Function Method

3.1.2.3 Efficacy of Lamps

The Efficacy of a lamp is defined as the lumens produced by a lamp plus the ballast system divided by the total watts of input power (including the ballast), expressed in lumens per watt. The higher the efficacy, the lesser the energy consumed by the lamp.

The comparative efficacies and environmental impacts of the lamps are provided in the table 10 below:

| Sr. No. | Lamp Type with Wattage | Efficacy Range (Lumens/ Watt) | Rated Life (Hours) | EOL Toxic effects |
|------------|---|----------------------------------|-----------------------|-------------------|
| 1. | Fluorescent Tube Lights (T12 & T8) | 34 – 57 | 5000-10000 | Mercury |
| 2. | Compact Fluorescent Lamps | 25 - 70 | 10000 | Mercury |
| 3. | Light Emitting Diode | 60 - 76 | Up to 50000 | NIL |
| 4. | Incandescent Halogen filament (low voltage) | 31 - 35 | 2000-3000 | NIL |
| 5. | Incandescent Tungsten filament | 6 - 15 | 1000 | NIL |

Table 10: Comparative efficacies and environmental impacts of lamps

3.1.2.4 Wall Window Ratio and lighting level

The overall **Wall to window ratio (WWR) is observed to be 21%.** During a detailed energy audit, lighting level was measured in some rooms randomly, to verify whether they are in accordance with NBC standards. In the random survey of lux levels at different places, it was found that **74%** of **the lux level** measurements are matching with the NBC norms, 15% were over-lit (mostly on the 3rd and fourth floor of main building), and 9% were underlit (these are spaces from extension building, as classroom have windows opening in corridors).

The results of the survey of Lux levels are shown below:

| Sr. No | Space | Avg Lux level | Lux level as per NBC | Remark |
|-----------|--------------|------------------|-------------------------|---------------|
| 1 | Room No. 01 | 350 | 200 - 300 - 500 | Within Limit |
| 2 | Room No. 02 | 340 | 200 - 300 - 500 | Within Limit |
| 3 | Room No. 03 | 350 | 200 - 300 - 500 | Within Limit |
| 4 | Room No. 04 | 330 | 200 – 300 - 500 | Within Limit |
| 5 | Room No. 05 | 310 | 200 - 300 - 500 | Within Limit |
| 6 | Room No. 08 | 340 | 200 - 300 - 500 | Within Limit |
| 7 | Room No. 12 | 480 | 200 – 300 - 500 | Within Limit |
| 8 | Room No. 17 | 430 | 200 – 300 - 500 | Within Limit |
| 9 | Room No. 21 | 580 | 200 - 300 - 500 | Exceeds Limit |
| 10 | Room No. 101 | 330 | 200 - 300 - 500 | Within Limit |
| 11 | Room No. 103 | 470 | 200 - 300 - 500 | Within Limit |
| 12 | Room No. 104 | 480 | 200 - 300 - 500 | Within Limit |
| 13 | Room No. 105 | 490 | 200 - 300 - 500 | Within Limit |
| 14 | Room No. 107 | 360 | 200 - 300 - 500 | Within Limit |
| 15 | Room No. 108 | 670 | 200 - 300 - 500 | Exceeds Limit |
| 16 | Room No. 110 | 340 | 200 - 300 - 500 | Within Limit |
| 17 | Room No. 113 | 530 | 200 - 300 - 500 | Exceeds Limit |
| 18 | Room No. 114 | 430 | 200 - 300 - 500 | Within Limit |
| 19 | Room No. 115 | 370 | 200 - 300 - 500 | Within Limit |
| 20 | Room No. 116 | 330 | 200 - 300 - 500 | Within Limit |

| 21 | Room No. 118 | 360 | 200 - 300 - 500 | Within Limit |
|----|--------------|-----|-----------------|---------------|
| 22 | Room No. 119 | 360 | 200 - 300 - 500 | Within Limit |
| 23 | Room No. 120 | 595 | 200 – 300 - 500 | Exceeds Limit |
| 24 | Room No. 121 | 530 | 200 – 300 - 500 | Exceeds Limit |
| 25 | Room No. 204 | 427 | 200 - 300 - 500 | Within Limit |
| 26 | Room No. 205 | 532 | 200 - 300 - 500 | Exceeds Limit |
| 27 | Room No. 206 | 360 | 200 - 300 - 500 | Within Limit |
| 28 | Room No. 207 | 330 | 200 - 300 - 500 | Within Limit |
| 29 | Room No. 208 | 340 | 200 - 300 - 500 | Within Limit |
| 30 | Room No. 209 | 402 | 200 - 300 - 500 | Within Limit |
| 31 | Room No. 211 | 330 | 200 - 300 - 500 | Within Limit |
| 32 | Room No. 213 | 492 | 200 - 300 - 500 | Within Limit |
| 33 | Room No. 214 | 350 | 200 - 300 - 500 | Within Limit |
| 34 | Room No. 217 | 340 | 200 - 300 - 500 | Within Limit |
| 35 | Room No. 218 | 330 | 200 - 300 - 500 | Within Limit |
| 36 | Room No. 219 | 430 | 200 - 300 - 500 | Within Limit |
| 37 | Room No. 301 | 670 | 200 - 300 - 500 | Exceeds Limit |
| 38 | Room No. 302 | 550 | 200 - 300 - 500 | Exceeds Limit |
| 39 | Room No. 303 | 660 | 200 - 300 - 500 | Exceeds Limit |
| 40 | Room No. 304 | 430 | 200 - 300 - 500 | Within Limit |
| 41 | Room No. 305 | 360 | 200 - 300 - 500 | Within Limit |
| 42 | Room No. 306 | 756 | 200 - 300 - 500 | Exceeds Limit |
| 43 | Room No. 307 | 640 | 200 - 300 - 500 | Exceeds Limit |
| 44 | Room No. 308 | 540 | 200 - 300 - 500 | Within Limit |
| 45 | Room No. 309 | 690 | 200 - 300 - 500 | Exceeds Limit |
| 46 | Room No. 310 | 630 | 200 - 300 - 500 | Exceeds Limit |
| 47 | Room No. 311 | 330 | 200 - 300 - 500 | Within Limit |
| 48 | Room No. 312 | 680 | 200 - 300 - 500 | Exceeds Limit |
| 49 | Room No. 313 | 542 | 200 - 300 - 500 | Exceeds Limit |
| 50 | Room No. 314 | 480 | 200 - 300 - 500 | Within Limit |
| 51 | Room No. 315 | 590 | 200 - 300 - 500 | Exceeds Limit |

| 52 | Room No. 316 | 330 | 200 - 300 - 500 | Within Limit |
|----|----------------|-----|-----------------|---------------|
| 53 | Room No. 317 | 510 | 200 - 300 - 500 | Exceeds Limit |
| 54 | Room No. 318 | 530 | 200 - 300 - 500 | Exceeds Limit |
| 55 | Room No. 319 | 340 | 200 - 300 - 500 | Within Limit |
| 56 | Room No. 320 | 330 | 200 - 300 - 500 | Within Limit |
| 57 | Room No. 321 | 410 | 200 - 300 - 500 | Within Limit |
| 58 | Room No. 402 | 570 | 200 - 300 - 500 | Exceeds Limit |
| 59 | Room No. 403 | 850 | 200 - 300 - 500 | Exceeds Limit |
| 60 | Room No. 404 | 966 | 200 - 300 - 500 | Exceeds Limit |
| 61 | Room No. 405 | 612 | 200 - 300 - 500 | Exceeds Limit |
| 62 | Room No. 407 | 720 | 200 - 300 - 500 | Exceeds Limit |
| 63 | Room No. G-24 | 270 | 200 - 300 - 500 | Within Limit |
| 64 | Room No. G-25 | 250 | 200 - 300 - 500 | Within Limit |
| 65 | Room No. G-27 | 540 | 200 - 300 - 500 | Exceeds Limit |
| 66 | Room No. G-28 | 542 | 200 - 300 - 500 | Exceeds Limit |
| 67 | Room No. G-29 | 520 | 200 - 300 - 500 | Exceeds Limit |
| 68 | Room No. G-30 | 530 | 200 - 300 - 500 | Exceeds Limit |
| 69 | Room No. E-101 | 230 | 200 - 300 - 500 | Within Limit |
| 70 | Room No. E-102 | 160 | 200 - 300 - 500 | Below Limit |
| 71 | Room No. E-103 | 180 | 200 - 300 - 500 | Below Limit |
| 72 | Room No. E-108 | 160 | 200 - 300 - 500 | Below Limit |
| 73 | Room No. E-109 | 140 | 200 - 300 - 500 | Below Limit |
| 74 | Room No. E-110 | 130 | 200 - 300 - 500 | Below Limit |
| 75 | Room No. E-201 | 160 | 200 - 300 - 500 | Below Limit |
| 76 | Room No. E-202 | 140 | 200 - 300 - 500 | Below Limit |
| 77 | Room No. E-203 | 160 | 200 - 300 - 500 | Below Limit |
| 78 | Room No. E-204 | 140 | 200 - 300 - 500 | Below Limit |
| 79 | Room No. E-205 | 196 | 200 - 300 - 500 | Below Limit |
| 80 | Room No. E-206 | 242 | 200 - 300 - 500 | Within Limit |
| 81 | Room No. E-207 | 210 | 200 - 300 - 500 | Within Limit |
| 82 | Room No. E-208 | 132 | 200 - 300 - 500 | Below Limit |

| 83 | Room No. E-209 | 212 | 200 - 300 - 500 | Within Limit |
|----|----------------|-----|-----------------|--------------|
| 84 | Room No. E-301 | 130 | 200 - 300 - 500 | Below Limit |
| 85 | Room No. E-302 | 140 | 200 – 300 - 500 | Below Limit |
| 86 | Room No. E-303 | 153 | 200 – 300 - 500 | Below Limit |
| 87 | Room No. E-304 | 116 | 200 – 300 - 500 | Below Limit |
| 88 | Room No. E-305 | 136 | 200 – 300 - 500 | Below Limit |
| 89 | Room No. E-306 | 240 | 200 - 300 - 500 | Within Limit |
| 90 | Room No. E-307 | 168 | 200 – 300 - 500 | Below Limit |
| 91 | Room No. E-308 | 170 | 200 – 300 - 500 | Below Limit |
| 92 | Room No. E-309 | 180 | 200 – 300 - 500 | Below Limit |
| 93 | Room No. E-310 | 230 | 200 – 300 - 500 | Within Limit |

Table 11: Summary of lux levels comparison with NBC

Summary of Observations: Lighting

- 1. There are in total **1317** lamps (artificial light sources) in the college buildings amounting to an annual energy consumption of **29,380kWh** constituting **27% of total energy consumption**.
- 2. 90% of lighting fixtures are LED.
- 3. The building envelope has a **Window Wall Ratio (WWR) of 21%,** which is within ECBC's allowable norms of up to 40%.
- 4. **84%** of the **spaces comply** with the **LPD norms** of ECBC. By the Space Function method, most of the key activity spaces meet the ECBC norms.
- 5. In the random survey of lux levels at different places, it was found that **74%** of **the lux level** measurements are matching with the NBC norms.
- 6. The highest lighting consumption is on the **Ground floor (29%)**, **First floor (27%)**, **and third floor (22%)** followed by **the Second floor (19%)** and the fourth floor 3%.
- 7. Currently, all the lights have to be manually switched off and switched on.

3.1.3 Energy Consumption for Thermal Comfort

Fans and Air Conditioning together consume **44%** of the energy consumption of the campus. Both these are required for the thermal comfort of occupants. Only **7%** of the college space is conditioned.




Figure 8: Conditioned and un-conditioned areas in Smt. Chandibai Himathmal Mansukhani college

There are in total 693 ceiling fans fitted in the audited area of the college.

1. Fans contribute **22**% (**24,067 kWh**) of the energy consumption. The ground floor has a maximum load of 27%. As 93% of the college spaces are naturally ventilated, all the floors have a similar load, except the fourth floor which has only 4 classrooms and 3 store rooms. The floor-wise break-up of fan consumption is provided in Figure 9 and Table 12.




Figure 9: Percentage breakup of Floor-wise Annual Energy Consumption of Fans

| Sr. No. | Floor | Total Consumption (kWh/year) |
|-------------|--------------|------------------------------|
| 1 | Ground floor | 6394 |
| 2 | First floor | 6009 |
| 3 | Second floor | 5189 |
| 4 | Third floor | 5540 |
| 5 | Fourth floor | 935 |
| Grand Total | | 24,067 |

Table 12: Total floor-wise annual energy consumption by Fans (kWh/year)

2. Air conditioning has the overall consumption amounting to 22% of the college total energy consumption, 20 TON of refrigeration and 23,826 units of electricity annually (2021-2022) as per calculated consumption. The comfort air-conditioning system at college mainly comprises split units. The ground floor has an auditorium, mini-conference and exam department room respectively while the first floor has air-conditioned administrative spaces and labs contributing to a major air conditioning load. The breakup of different indoor units and the floor-wise consumption of AC is shown in Fig 10 and Table 13. Detailed parameters of the AC are shown in Table 14.




Figure 10: Percentage breakup of Floor-wise Annual Energy Consumption of AC

| Sr. No. | Building | Total Consumption (kWh/year) |
|-------------|--------------|------------------------------|
| 1 | Ground floor | 6872 |
| 2 | First floor | 16170 |
| 3 | Second floor | 784 |
| Grand Total | | 23,826 |

Table 13: Total floor-wise AC consumption (kWh/year)

| Sr. | Parameters | Auditorium (Extension building) | | | | |
|-----|-------------------------------------|---------------------------------|-----------|-----------|-----------|--------|
| No. | r at affecter 5 | AC unit-1 | AC unit-2 | AC unit-3 | AC unit-4 | AC -5 |
| 1 | Make | Voltas | Voltas | Voltas | Voltas | Voltas |
| 2 | Capacity (TR) | 2.12 | 2.12 | 2.12 | 2.08 | 2.12 |
| 3 | Cooling Effect Delivered (TR) | 0.54 | 0.35 | 0.78 | 0.32 | 1.08 |
| 4 | Power Consumption (kW) | 1.58 | 1.43 | 1.72 | 1.90 | 3.10 |
| 5 | Specific energy consumption (kW/TR) | 2.9060 | 4.0551 | 2.2172 | 5.9774 | 2.8650 |
| 6 | Energy Efficiency Ratio | 1.21 | 0.87 | 1.58 | 0.59 | 1.23 |

| Sr. | Parameters | Server Room | | 107-IT Lab | |
|-----|------------------------------------|-------------|-----------|------------|-----------|
| No | | AC unit-1 | AC unit-2 | AC unit-1 | AC unit-2 |
| 1 | Make | Daikin | Daikin | Voltas | Voltas |
| 2 | Capacity (TR) | 1.16 | 1.16 | 1.62 | 1.74 |
| 3 | Cooling Effect Delivered (TR) | 0.41 | 0.44 | 0.80 | 0.36 |
| 4 | Power Consumption (kW) | 0.85 | 0.90 | 2.50 | 1.76 |
| 5 | Specific energy consumption(kW/TR) | 2.0782 | 2.0595 | 3.1116 | 4.9244 |
| 6 | Energy Efficiency Ratio | 1.69 | 1.70 | 1.13 | 0.71 |

| Sr. | Parameters | Exam Room | 108-Vice Principal Office | | ffice |
|-----|------------------------------------|-----------|---------------------------|-----------|-----------|
| No | | AC unit-1 | AC unit-1 | AC unit-2 | AC unit-3 |
| 1 | Make | Voltas | Voltas | LG | Onida |
| 2 | Capacity (TR) | 1.74 | 2.12 | 1.05 | 1.14 |
| 3 | Cooling Effect Delivered (TR) | 1.11 | 0.41 | 0.22 | 0.22 |
| 4 | Power Consumption (kW) | 1.38 | 1.50 | 1.09 | 0.99 |
| 5 | Specific energy consumption(kW/TR) | 1.2408 | 3.6987 | 4.8550 | 4.4756 |
| 6 | Energy Efficiency Ratio | 2.83 | 0.95 | 0.72 | 0.78 |

| Sr. | Parameters | Mini-Conference room | | Principal Office | |
|-----|------------------------------------|----------------------|-----------|------------------|-----------|
| No | | AC unit-1 | AC unit-2 | AC unit-1 | AC unit-2 |
| 1 | Make | Voltas | Voltas | Voltas | Voltas |
| 2 | Capacity (TR) | 1.69 | 1.69 | 1.67 | 1.67 |
| 3 | Cooling Effect Delivered (TR) | 0.89 | 0.79 | 0.49 | 0.35 |
| 5 | Power Consumption (kW) | 1.32 | 1.25 | 1.10 | 1.18 |
| 6 | Specific energy consumption(kW/TR) | 1.4861 | 1.5862 | 2.2488 | 3.3244 |
| 7 | Energy Efficiency Ratio | 2.36 | 2.21 | 1.56 | 1.06 |

Table 14: Details of audited AC units with their Performance parameters

The college uses 20 Tonnage of ACs in total which includes AC for Auditorium, Principal's cabin, computer lab, Vice principal cabin etc. The overall performance of AC compared to the (Bureau of Energy Efficiency) Energy Efficiency Ratio(EER), as shown in table 15 is critical, as they are performing well below the standards, contributing to energy losses. The efficiency of some units is very poor and needs complete overhauling of the unit

(From 1st January, 2018 to 31st December, 2020)

| Indian Seasonal Energy Efficiency Ratio (kWh/kWh) | | | |
|--|---------|---------|--|
| Star level | Minimum | Maximum | |
| 1 Star | 3.1 | 3.29 | |
| 2 Star | 3.3 | 3.49 | |
| 3 Star | 3.5 | 3.99 | |
| 4 Star | 4.0 | 4.49 | |
| 5 Star | 4.5 | | |

Table 15: Energy efficiency ratio as specified by BEE for split AC

Summary of Observations:

- **1.** The college has Ceiling fans whose energy consumption account for only **22** % of the total annual consumption.
- 2. The overall fan consumption shows that the ground floor has a maximum load of 27%. As 93% of the college spaces are naturally ventilated, all the floors have a similar load, except the fourth floor which has only 4 classrooms
- 3. Although only 7% of the built area, it contributes to 22% of the total energy consumption.
- 4. The overall air conditioning consumption shows that maximum usage is by the **First floor– 68%,** followed by **ground floor -29%** and second floor at 3%. This is because, first floor has air-conditioned administrative spaces and labs. Ground floor has an auditorium, exam section and mini-conference room.
- 5. The performance of ACs is poor, can be improved with proper maintenance and chemical cleaning.

3.1.4 Equipment Energy Consumption

Equipment contributes **29%** of the total energy consumption. Major equipment includes Fridge, computers, microwave, projector, water pump, desktops etc. The detailed break-up of energy consumed by equipment is shown below.




Figure 11: Types of equipment

| Name of Equipment | Sum of Total usage kWh/year | No. of Equipment |
|----------------------|--------------------------------|------------------|
| Autoclave | 2650 | 5 |
| Centrifuge | 210 | 6 |
| Colourimeter | 365 | 10 |
| Computer /Laptop | 5159 | 146 |
| CRO | 121 | 7 |
| Distillation Unit | 153 | 2 |
| Electrophoretic Unit | 65 | 2 |
| Exhaust Fan | 36 | 2 |
| Flame Photometer | 0 | 1 |
| Fridge | 8410 | 12 |
| Heating Coils | 55 | 5 |
| Incubator | 8629 | 11 |

| Laminar | 77 | 2 |
|---------------------|-------|-----|
| Magnetic Stirrer | 23 | 3 |
| Microscope | 0 | 1 |
| Muffle furnace | 4 | 1 |
| Oven | 4075 | 15 |
| pH Meter | 248 | 10 |
| Printer | 36 | 5 |
| Small fridge | 90 | 1 |
| Spectrophotometer | 43 | 2 |
| Water Bath | 923 | 8 |
| Wax melting machine | 20 | 1 |
| Weighing Balance | 203 | 10 |
| Pumps | 1 | 2 |
| Biometrics | 4 | 3 |
| Grand Total | 31599 | 271 |

Table 16: Type of Equipment and their annual usage




Figure 12: Percentage breakup of Floor-wise Annual Energy Consumption of Equipment

| S. No. | Floor | Total Consumption (kWh). |
|--------|--------|--------------------------|
| 1 | Ground | 748.00 |
| 2 | First | 5518.34 |
| 3 | Second | 25332.52 |
| Total | | 31,599 |

Table 17: Total floor-wise Equipment consumption (kWh/year)

3.1.4.1. Pumps and Motors

There are 4 pumps, of which 2 were non-functional during the audit. One pump is use to pump municipal water supply for all the domestic requirements except flushing from the underground tank to overhead tank. For the flushing requirement, 1 pump is fitted over the borewell.

| S. No. | Item Description | Capacity | Usage | Power (kW) |
|--------|------------------|----------|----------------|------------|
| 1 | Water Pump | 7.5 HP | 0.5 hours/day | 6.21 |
| 2 | Water Pump | 5 HP | 2 hours/day | 3.47 |
| 3 | Water Pump | 1 HP | Non functional | |
| 4 | Water Pump | 1 HP | Non functional | |

Table 18: Detail of the pumps

Some of the equipment used in the college are shown in the pictures below:







Plate 13: Biology lab- Incubators

Plate 14: Computer lab

Plate 15:Auditorium having projectors

Summary of Observations: Equipment

- 1. Total energy consumption by equipment is **29%**.
- 2. The energy consumption by equipment is primarily through **incubator and Fridge** is 27% each, **Computers** is 16%, **oven** is 12%. **Autoclave** is 8%.
- 3. The largest consumption of energy concerning equipment is on the **Second floor** is **80%**, the **first floor** is **18%**, followed by the **ground floor- 2%**. This was mainly due to various labs are on the second floor.

3.1.5 Electrical system study and leakage currents

The main supply wires were studied for their capacity and size, they were found to be adequate to serve the purpose as seen in table 19.

| Cr. No. | Docariation Cable Size | | Cu | rrent per Pha | Remark | |
|-----------|-----------------------------|--------------------------------|---------|---------------|----------|----------|
| Sr. No De | Description | Cable Size | R | Υ | В | Kemark |
| 1 | Source-1(Main Building) | 3.5C x 240 sq. mm Al. Cable | 35.1Amp | 45.8mp | 49.7Amp | Adequate |
| 2 | Source-2(Main Building) | 3.5C x 240 sq. mm Al. Cable | 55.3Amp | 44.55Amp | 71.4Amp | Adequate |
| 3 | Extension Building | 3.5C x 120 sq. mm Al. Cable | 23.6Amp | 23.59Amp | 37.42Amp | Adequate |


Table 19: Study of main supply cables

Thermal imaging of the electrical power distribution was done to detect hot spots – likely to cause failures. Temperature readings above 60°C, are of concern (highlighted in Yellow) and repairs to those spots are necessary.

| Sr No | Description Temperature in °C | | Remark | | | | | | |
|--------------------|--|----------------|--------------------------------------|--|--|--|--|--|--|
| | Main Building | | | | | | | | |
| Changeover Panel-2 | | | | | | | | | |
| 1 | 1 250Amp Input 32.2 Temperature Within Permissib | | | | | | | | |
| 2 | 200Amp Floor panel | 32.3 | Temperature Within Permissible Limit | | | | | | |
| | | Changeover Pan | el-1 | | | | | | |
| 3 | 250Amp Input | 29.2 | Temperature Within Permissible Limit | | | | | | |
| 4 | 200Amp Floor panel | 36.7 | Temperature Within Permissible Limit | | | | | | |
| 5 | 3rd floor main-125Amp | 30.8 | Temperature Within Permissible Limit | | | | | | |
| | | Main Buildin | g | | | | | | |
| 6 | 1F1-200Amp Panel-1 | 31.2 | Temperature Within Permissible Limit | | | | | | |
| 7 | 1F2-100Amp VTPN DB | 30.8 | Temperature Within Permissible Limit | | | | | | |
| 8 | 1F3-100Amp VTPN DB F1 | 30.9 | Temperature Within Permissible Limit | | | | | | |
| 9 | 1F4-100Amp VTPN DB S1 | 30.2 | Temperature Within Permissible Limit | | | | | | |
| 10 | 1F5-100Amp VTPN DB T1 | 30.5 | Temperature Within Permissible Limit | | | | | | |
| 11 | 1F6-100Amp MCCB | 36.5 | Temperature Within Permissible Limit | | | | | | |
| 12 | 1F1-200 C/O Panel-2 | 32.5 | Temperature Within Permissible Limit | | | | | | |
| 13 | 1F2-100Amp VTPN G2 | 33.1 | Temperature Within Permissible Limit | | | | | | |
| 14 | 1F3-100Amp VTPN F2 | 33.9 | Temperature Within Permissible Limit | | | | | | |
| 15 | 1F4-100Amp VTPN S2 | 31.5 | Temperature Within Permissible Limit | | | | | | |
| 16 | 1F5-100Amp VTPN T2 | 31 | Temperature Within Permissible Limit | | | | | | |
| 17 | GF Mini Conference room | 29.7 | Temperature Within Permissible Limit | | | | | | |
| 18 | GF VTPN DB-1 | 29.8 | Temperature Within Permissible Limit | | | | | | |
| 19 | GF LDB-1 | 28.8 | Temperature Within Permissible Limit | | | | | | |

| 20 | GF VTPN-2 | 33.3 | Temperature Within Permissible Limit |
|----|--------------------------|-----------------------|--------------------------------------|
| 21 | GF LDB-2 | 49.6 | Temperature Above Permissible Limit |
| 22 | 1st Floor DB-2 | 38 | Temperature Within Permissible Limit |
| 23 | 1st Floor LDB-40Amp Main | 30.4 | Temperature Within Permissible Limit |
| 24 | 1F VTPN -1 | 30.5 | Temperature Within Permissible Limit |
| 25 | 1F LDB | 30.8 | Temperature Within Permissible Limit |
| 26 | 2F VTPN DB-1 | 34.3 | Temperature Within Permissible Limit |
| 27 | 2F LDB-1 | 30 | Temperature Within Permissible Limit |
| 28 | 2F VTPN DB-2 | 31.8 | Temperature Within Permissible Limit |
| 29 | 2F LDB | 30.8 | Temperature Within Permissible Limit |
| 30 | 3F VTPN-1 | 30.1 | Temperature Within Permissible Limit |
| 31 | 3F LDB-1 | 30.2 | Temperature Within Permissible Limit |
| 32 | 3F VTPN DB-2 | 90.7 | Temperature Above Permissible Limit |
| 33 | 3F LDB-2 | 31.2 | Temperature Within Permissible Limit |
| 34 | 4F Terrace DB | 27.8 | Temperature Within Permissible Limit |
| | | Extension Buil | ding |
| 35 | VTPN DB | 28.5 | Temperature Within Permissible Limit |
| 36 | LDB | 32.5 | Temperature Within Permissible Limit |
| 37 | Emergency DB | 29.2 | Temperature Within Permissible Limit |
| 38 | DG Fuse-200Amp | 35.8 | Temperature Within Permissible Limit |
| 39 | Main Fuse-200Amp | 63 | Temperature Above Permissible Limit |
| 40 | Main Changeover switch | 106.3 | Temperature Above Permissible Limit |
| 41 | GF Office | 30.7 | Temperature Within Permissible Limit |
| 42 | THM Hall DB | 38.3 | Temperature Within Permissible Limit |
| | | Main Buildir | ng |
| 43 | GF ELDB | 28.4 | Temperature Within Permissible Limit |
| 44 | ELDB-1 | 30.2 | Temperature Within Permissible Limit |
| 45 | ELDB-2 | 28.1 | Temperature Within Permissible Limit |
| 46 | ELDB-3 | 28.6 | Temperature Within Permissible Limit |

Table 20: Results of thermal imaging of distribution panels




7/7/2022 12:31:56 PM Temperature Above Permissible Limit



ioibio Ligiti iiilago

3F VTPN DB-2




IR_02012.IS2

7/7/2022 1:31:22 PM Temperature Above Permissible Limit



Visible Light Image

Main Changeover switch




IR_02020.IS2

7/7/2022 3:14:53 PM Temperature Above Permissible Limit



Visible Light Image

Main Fuse-200Amp



7/7/2022 3:14:27 PM Temperature Above Permissible Limit



Visible Light Image

| Sr. | | Earth | ing | |
|------|-------------------------------|------------|----------|---|
| No. | Description | Resistance | Current | Remark |
| 140. | | in Ω | in Amp | |
| | | Main | Building | |
| 1 | Main Building DG Neutral | 22.1 | 0 | Earth resistance found above permissible limit. |
| 2 | Extension Building DG Body | 5.7 | 0.59 | Earth resistance found above permissible limit. |
| 3 | Extension Building DG Neutral | 3.8 | 5.8 | Earth resistance found above permissible limit. |
| 4 | Main Building Main Panel | 0.01 | 24.1 | Within permissible limit. |
| 5 | GF Mini conference room DB | 0.1 | 32.4 | Leakage current found above permissible limit |
| 6 | GF LDB-1 | 830 | 0 | Earth resistance found above permissible limit. |
| 7 | GF VTPN DB-2 | 1.1 | 0.3 | Within permissible limit. |
| 8 | GF LDB-2 | 1.2 | 7.4 | Within permissible limit. |
| 9 | 1st Floor DB-2 | 0.79 | 10.4 | Within permissible limit. |
| 10 | 1st Floor LDB-40Amp Main | 0.91 | 12.3 | Within permissible limit. |
| 11 | 1F VTPN -1 | 0.023 | 5.2 | Within permissible limit. |
| 12 | 1F LDB | 0.022 | 5.6 | Within permissible limit. |
| 13 | 2F VTPN DB-1 | 0.017 | 1.7 | Within permissible limit. |
| 14 | 2F LDB-1 | 0.018 | 1.8 | Within permissible limit. |
| 15 | 2F VTPN DB-2 | 0.016 | 20.1 | Within permissible limit. |
| 16 | 2F LDB | 0.017 | 18.1 | Within permissible limit. |
| 17 | 3F VTPN-1 | 0.015 | 29.4 | Within permissible limit. |
| 18 | 3F LDB-1 | 0.018 | 30.1 | Within permissible limit. |
| 19 | 3F VTPN DB-2 | 0.017 | 0.7 | Within permissible limit. |
| 20 | 3F LDB-2 | 0.016 | 0.59 | Within permissible limit. |
| 21 | 4F Terrace DB | 0.015 | 29.1 | Within permissible limit. |
| 22 | Earth pit No-1 | 0.023 | 5.2 | Within permissible limit. |

Table 21:Earth Resistance measurement

| Sr. No | Images | Description |
|-----------|--|--|
| 1 | | Neutral to earth voltage for main building and extension building incomers is found very high i.e. (44.7V) than the standard limits. |
| 2 | | Cable joint found in between MSEB meter to Main Outgoing MCCB of all the three sources. |
| 3 | THE CONTRACT OF THE CONTRACT O | DG set installed for extension building, has it's canopy rusted, need to be attended. |
| 4 | | MSEDCL transformer installed in CHM college premises, LV Side cable bushings found in open condition. |

| 5 | Shot state of the | Insulated rubber mat is not provided in front of main panel of Main Building and extension building. |
|---|---|---|
| 6 | Contract by presenting | MSEB main panel installed inside transformer compartment cable terminations found in open condition would suggest providing shrouding for the same. |
| 7 | | Loose and hanging cables found near extension building main electrical installation. Unwanted/ Combustible material near electrical installation. |
| 8 | A | During socket testing, phase and neutral were found reversed for few sockets, and wiring corrections suggested. |
| 9 | | During socket testing, Earthing found faulty for both the building all floor sockets installed. |

Sparking observed inside the extension building main changeover switch, need to be attend the same.

Gland plate opening holes found in Main panel and distribution board, need to be sealed the same by using rubber grommets.

Table 22: Observations with actual images

3.1.6 Benchmarking - Energy Performance Index (EPI)

The **Energy Performance Index (EPI)** of Smt. Chandibai Himathmal Mansukhani college **is 7.86 kWh/sq. m/year** in 2021-2022 as the billing data. As per the **Bureau of Energy Efficiency (BEE) EPI benchmark for institutional** buildings in **warm-humid climate zone** (such as Mumbai) is **150 kWh/sq. m/year.** The energy consumption of the college is well below this benchmark, as the college was fully functional for around 3 months, due to the Covid pandemic.

| Climate Zone | EPI (kWh/m²/yr) |
|--------------|-----------------|
| Warm & Humid | 150 |
| Composite | 117 |
| Hot & Dry | 106 |
| Moderate | 129 |

Table 23: EPI benchmark by BEE for Institutes

3.1.7 Benchmarking – Specific Energy Consumption (SEC)

Specific Energy Consumption (SEC) is defined as the energy consumption per unit product. The specific energy consumption considering students, faculty and staff members was calculated to form a benchmark of **8.43 kWh/ person/ year** and **Rs. 156** per person per annum (considering 2021 data).

3.1.8 Billing Analysis and Metering system

- 1. The energy consumption in the college is mainly in the form of electricity which is supplied through **Maharashtra State Electricity Distribution Co. Ltd**
- 2. The College has three connections billed under the category LT II B commercial.
- 3. The Tariff Structure of the Utility company along with the additional Time of Day (TOD) tariff is summarized in the table 24 below:

| Tariff | Meter No | Contract | Fixed Demand | Energy | Wheeling | Overall |
|--------------|--------------|----------|-----------------|--------|----------|----------|
| Category | | Demand | charge ₹/Month | charge | charge | Cost per |
| | | kVA | | ₹/Unit | ₹/Unit | Unit |
| LT II B | 055-X1152120 | 45 | Rs. 427 per kVA | 6.00 | 1.46 | 18.48 |
| (Commercial) | 055-X1152119 | 45 | | | | |
| | 055-X1130747 | 47 | | | | |

Table 24: Tariff Structure as per the Mahadiscom for Year 2022

- 4. The fixed charges of the commercial meters are quite high.
- 5. The overall per unit charge is Rs. 18.48 per unit.
- 6. It is observed that the annual energy consumption of the college as per electricity bills is **95,498kWh** for the Year **Jun 2021 May 2022.** The average monthly consumption is approximately **7,958 units.**

It can be seen that March, April and May 2022 have the highest consumption. This could be attributed to excessive discomfort and use of fans and ACs due to higher insolation and relative humidity. The college was fully functional only for around 3 months, due to the Covid pandemic. Although May month has vacations, building repair and renovation works were in progress.




Figure 13: Monthly billed units by meter

3.2 Water

The College has 2 OHT of a capacity of in total of **40,000** and a UGT of capacity **36,000 litres**. There are 17 wash basins (located in washrooms), and 22 WC have single flush type flushing tanks of which 4 are Indian water closets with ablution taps and a total of 3 drinking water coolers.

Considering 11,326 people at a rate of 45 litres per person per day (as per NBC), the maximum total **daily** requirement of the college is **509.67** kilo litres (227 kLD domestic and 283kLD flushing) This is shown in table no. 25. Monthly requirement should be **11,722** kilo litres considering **23 days** of operation per month.

| Category | Number of Occupants | Water requirement per person (LPCD) | | | Total water requirement (LPCD) | | | |
|----------------------|---------------------------|--|----|----|--------------------------------|----------|--------|--|
| | | Domestic Flushing Total | | | Domestic | Flushing | Total | |
| Students | 10975 | 20 | 25 | 45 | 219500 | 274375 | 493875 | |
| Teachers | 171 | 20 | 25 | 45 | 3420 | 4275 | 7695 | |
| Non-teaching staff | 173 | 20 | 25 | 45 | 3460 | 4325 | 7785 | |
| Administrative staff | 7 | 20 | 25 | 45 | 140 | 175 | 315 | |
| Total | 11326 | | | | 226520 | 283150 | 509670 | |
| Total in KLD | | | | | 226.52 | 283.15 | 509.67 | |

Table 25: Total water usage of the Campus

However, as per water bills submitted by the college, the average monthly water consumption is **457 kilo litres**, which means daily consumption is around **20 kilo litres**. This amounts to only **9%** of the calculated domestic daily water consumption. The exact daily consumption can be observed in figure 14.

The college has the municipal water connection whose meter is not working for the entire last year, as per bills. They also have three private connections of water supply in addition to active borewells, which are not metered.

The College campus water bill shows that the **average monthly water charges are Rs. 1715.08/-**, accordingly the **per kilolitre of water cost is around Rs. 22/-**.

Table no. 26 gives details of the faucets, flushing devices and water coolers in the College.

| S. No | Building | Floor | Type of toilet block | Total no. Of toilet blocks | Drinking water/ cooler | Water closet (wc) | Urinals | Wash basin taps | Flushing tank | Type of flushing tank (dual flush/ single flush) | Remark |
|----------|---------------------|--------|-------------------------|-------------------------------------|------------------------------|--|---------|-----------------------|------------------|---|------------------------------------|
| 1 | | Ground | Ladies washroom | 1 | 1 | 2 | Nil | 1 | 2 | Single | One of Indian and one western type |
| 2 | Building 1 (main | Ground | Mini conference | 1 | Nil | 1 | Nil | 1 | 1 | Single | Western |
| 3 | building) | Ground | Gents washroom | 2 | Nil | 1+1 (Universal access toilet) | 1+4 | 1+2 | 2 | Single | Both are western type |
| 4 | | First | Gents washroom | 1 | 1 | 2 | 3 | 1 | 2 | Single | |
| 5 | | First | Principal office | 1 | Nil | 1 | Nil | 1 | 1 | Single | Western |

| 6 | | Third | Ladies washroom | 1 | 1 | 2 | Nil | 1 | 2 | Single | One is Indian and one is western type |
|----|----------------------|--------|---------------------|---|-----|---|-----|---|---|--------|---------------------------------------|
| 7 | | Third | Gents washroom | 1 | Nil | 1 | 1 | 1 | 1 | Single | |
| 8 | | Ground | Ladies washroom | 1 | Nil | 2 | Nil | 1 | 2 | Single | Both are western type |
| 9 | Building 2 | Ground | Gents washroom | 1 | Nil | 3 | 1 | 1 | 3 | Single | |
| 10 | (extension building) | First | Ladies washroom | 1 | Nil | 4 | Nil | 2 | 4 | Single | Two western, two Indian |
| 11 | | First | Gents washroom | 1 | Nil | 1 | Nil | 1 | 1 | Single | Western |
| 12 | | Second | Ladies' washroom | 1 | Nil | 2 | Nil | 1 | 1 | Single | One western, one Indian |
| 13 | | Second | Gents' washroom | 1 | Nil | 2 | | 1 | 1 | Single | Both western |
| 14 | | Third | Gents' washroom | 1 | | 1 | | 1 | 1 | Single | Western |

Table 26: Details of faucets, flushing devices and water coolers in the College.

3.2.1. Rain Water Harvesting

As per the data submitted by the college, it had a rainwater harvesting system wherein down take pipes collecting water from the rooftop catchment, was connected to a drain in the borewell., to facilitate groundwater recharge. At the time of audit, some of the down take pipes were disconnected from the drains, and in a few places the drains were clogged due to renovation work at college. The college is planning to restore the system.

3.3 Solid Waste

The college generates Paper, Glass, Cardboard, Cloth, Electrical and Electronic waste is collected in different bins i.e waste is segregated at source. This mainly constitutes to **50% of recyclable solid waste**, while **50% of organic** waste is generated by food waste from the canteen and leaf litter which can be composted on site.

The college had developed an E-waste collection system in collaboration with Eco friend industries, (a government approved E waste disposal facility) to facilitate periodically collection of E-waste. The college also facilitated recycling of paper waste generated in the academic year, by selling it to the waste to manager. (Certificate is provided in annexure F)

An incinerator for disposal of sanitary napkins, is available in one of the toilets on the 1^{st} floor. Awareness regarding the instrument is needed to use it effectively.

The college also had vermicomposting pits which were later changed to organic composting. During the lockdown, it was not maintained.









Plate 16: Incinerator located in ladies toilet

Plate 17: Bins for segregation of waste at source

3.4 Environment Quality

The college has created a Botanical and Butterfly Garden which was partially destroyed during the lockdown, it has a wide variety of trees which shade the south façade, some trees are as high as the second floor. Some trees are older than the establishment itself, while others were planted by faculty who have since moved on. The college has generated QR code for the campus trees, scanning which a detail information regarding the tree can be obtained by the user.





Plate 18:QR coding of the trees on campus

The department of Botany of Smt. CHM college has always been keen on maintaining a record of the greenery of the campus. A green census is a yearly practice of the department where the students of botany are educated and updated about the various tree species, their identification, method of propagation and use. The study has recorded a total of 308 trees and shrub species on the campus. The green census report is added as Annexure E. The college is located next to the river, facilitating various birds, insects etc, an overall good biodiversity, for example, 24 different birds are seen on the campus, as listed below.



Plate 19: Butterfly Garden

Plate 20 : Vegetation in front of main building

Plate 21: Botanical garden

The list of birds observed on the campus, submitted by the college is given below:

| S. No | Observed on campus - Birds |
|-------|----------------------------|
| 1 | Asian Koel |
| 2 | Black Kite |
| 3 | Coppersmith Barbet |
| 4 | Crow |
| 5 | Cuckoo |
| 6 | White throated Kingfisher |
| 7 | Lesser Egret |
| 8 | Pond Heron |
| 9 | Pigeon |
| 10 | Rose Ringed Parakeet |
| 11 | Sparrow |
| 12 | Scaly Breasted Munia |

| S. No | Observed on campus - Birds |
|-------|----------------------------------|
| 13 | Red Vented Bulbul |
| 14 | Asian Pied Starling |
| 15 | Common Myna |
| 16 | Indian Golden Oriole [Migratory] |
| 17 | Little Cormorant |
| 18 | Cattle Egret |
| 19 | Green Bee-eater |
| 20 | White throated fantail |
| 21 | Black Drongo [Migratory] |
| 22 | Common Raven |
| 23 | Oreintal Magpie-Robin |
| 24 | Purple-rumped Sunbird |



Plate 22: Oreintal Magpie-Robin



Plate 23: White throated Kingfisher



Plate 24: Coppersmith Barbet



Plate 25: Rose Ringed
Parakeet

4. Recommendations for Green Campus and Feasibility for Smt. Chandibai Himathmal Mansukhani college

4.1 Visual Comfort and Energy Efficiency

The Light power density values in educational spaces such as classrooms are found to be meeting the maximum norms as prescribed by ECBC 2017. However, all spaces correspond to satisfactory illumination levels as measured during the random lux level survey of spaces. The overall lighting consumption is meeting the ECBC norms. It is therefore prescribed to improve the energy efficiency of the illumination levels following measures can be implemented

4.1.1 Replacement of T8 (36W) Fluorescent Tube Lights (FTLs) along with electromagnetic ballast with 18W LED Tube Lights having a lumen output of 1800 (efficacy = 100 Lumens per Watt)

Since 36W Fluorescent Tube Lights (FTLs) are the largest source of lighting energy consumption, they should be replaced with efficient 18W LED T8 tube lights of 1800 lumens output (efficacy of 100 L/W) with a long life of 40,000 hours, diffused uniform light output, better colour rendering (CRI>83) suitable for learning spaces and built-in

protection circuit.

Plate 26: Existing 36W
Fluorescent Tube Lights



Plate 27: Proposed 18W LED Tube Lights of 1800 Lumens output (efficacy = 100 L/

| | Areas app | licable: All c | lassrooms, | staffroom, | conference | | uter lab, | cabins | | |
|-----------------------------------|----------------------|------------------------------|--------------------------------------|----------------------|-------------------------------|-----------------------------|-----------------------|----------------------------|----------------------------|---------------------------|
| Existing Type of Light | Existing Quantity | Existing Wattage (kWh) | Proposed type of Light | Proposed Quantity | Estimated Wattage (kWh) | Rate per unit (Rs) | Total Cost (Rs) | Annual Savings (kWh) | Annual Savings* (Rs) | Pay back in year |
| 36 W Fluorescent tube light | 132 | 4656.96 | 18W LED (t8) of 1800 Lumens | 132 | 1552.32 | 345 | 45,540 | 3105 | ₹57,374 | 1 |

Table 27: Table for calculation of Replacement of tube lights and LED lights

4.1.2 Optimization of outdoor lights operation based on Astronomical timer

| Energy efficiency improvement measures | Investment Rs. In |
|--|-------------------|
| | Lakh |
| Optimization of street light operation based on Astronomical timer | 0.10 |

Table 28: Energy efficiency improvement measures

Most of the switching points are manually operated to switch ON and OFF the lighting system. The operating schedule is as per the table mentioned below;

| Sr No | Season | Switch ON time | Switched OFF time |
|-------|---------|----------------|-------------------|
| 1 | Summer | 6.30 PM | 6.00 AM |
| 2 | Winter | 5.30 PM | 7.00 AM |
| 3 | Monsoon | 6.00 PM | 6.30 AM |

Time Switches are used to control events concerning real-time clock (RTC) whereas timers are used to control processing times. Therefore, RTC forms the basic difference between timer and time switch functionality.

With the help of Time switches it is possible to switch ON and OFF devices like lights, heaters, etc. automatically at the desired time of the day/night thereby giving the advantage of convenience and reduction in power wastage or substantial energy savings. The need for automation in the street light system is for accurate switching of lights at sunset or twilight sunset and switch OFF at sunrise or twilight sunrise, avoiding the human error to operate the switch, thereby providing energy savings.



Figure 14: Time Switches

4.2 Thermal Comfort and Energy Efficiency

4.2.1 Replacement of regular fans with BEE star-rated fans and Brushless Direct Current (BLDC) fans

| Repla | Replacement Details: Regular fans with BEE star-rated fans or Brushless Direct Current | | | | | | | | | | |
|----------------------------|--|------------------------------|----------------------------|----------------------|-------------------------------|--|------------|----------------------------|----------------------------|--------------|--|
| | (BLDC) fans | | | | | | | | | | |
| | Areas applicable: Classrooms, office, computer lab, staff room, cabins | | | | | | | | | | |
| Existing Type of Fan | Existing Quantity | Existing Wattage (kWh) | Proposed type of Fan | Proposed Quantity | Estimated Wattage (kWh) | Rate per unit based on exchange policy of Utility | Total Cost | Annual Savings (kWh) | Annual Savings* (Rs) | Pay- back | |
| | | | | | | (Rs) | (Rs) | | | | |
| Ceiling Fans 53 W | 693 | 24067 | Atomberg Gorilla 32W | 693 | 14531 | 3,000 | 20,79,000 | 9,536 | 1,76,225. 83 | 11.8 | |

Table 29: Replacement of Regular fans with BEE star rated/Brushless Direct Current (BLDC) fans.

The cost and payback period for fans is according to market value, i.e. purchased from the vendor. The vendor list is provided in Annexure H.



Plate 28: Existing Ceiling Fan of 60 W



Plate 29: Proposed Ceiling Fan of Atomberg Gorilla 32W

4.2.2 AC maintenance

Currently, the ACs are performing in good condition as per the audit. However, regular maintenance is necessary. In case any AC is being replaced or new ACs are purchased, the college should opt for BEE 3 or 5-star rated ACs only for superior performance and energy efficiency. We recommend the use of Airtron AC energy-saving devices for all split and window AC units, especially those which are being used frequently. With its patented dual-sensor driver microprocessor technology, it can save up to 35% of energy consumption of an AC unit.

4.3 Recommendations for Solar PV system

College should install Solar PV system to harness renewable solar energy. Then college has has to collaborate with Utility (Mahadiscom) to introduce a net metering system so that there is the scope of wheeling the power back to the Grid by way and accounting for it in the College electricity bills. **This can provide a reduction in electricity bills by 15-20% to the College.**



Plate 30: Picture showing the proposed Solar PV panels

Calculations of the solar photovoltaic installation are done using SPIN (An online portal for solar photovoltaic Installation) developed by the Ministry of New & Renewable energy. The Solar rooftop calculator shows the following statistics;

- \bullet Average solar irradiation in MAHARASHTRA state is 1266.52 W / sq.m
- 1kWp solar rooftop plant will generate on an average over the year 5.0 kWh of electricity per day (considering 5.5 sunshine hours)

| 1. Size of Power Plant | |
|---|---------------------|
| Feasible Plant size as per your Roof Top Area : | 38.3kW |
| 2. Cost of the Plant : | |
| MNRE current Benchmark Cost (without GST) : | Rs. 38236 Rs. / kW |
| Without subsidy (Based on the current MNRE benchmark) : | Rs. 14,64,439 |
| 3. Total Electricity Generation from Solar Plant : | |
| Annual : | 57,450kWh |
| Life-Time (25 years): | 14,36,250kWh |
| 4) Financial Savings : | |
| Tariff @ Rs.18.48/ kWh (for top slab of usage) - No increase as | ssumed for 25 years |
| Monthly: | Rs. 88,473 |
| Annually: | Rs. 10,61,676 |
| Life-Time (25 years) : | Rs. 2,65,41,900 |

Table 30: Solar Rooftop plant calculation

4.4 General Recommendations and best practices for energy conservation

General recommendations:

- o A separate energy meter for each floor is also recommended. In the long run, a separate meter for light, fan, equipment and AC is recommended. This can also be connected to an IOT system to make it online so that energy consumption can be monitored on a real-time basis. Vendor details are shared in Annexure H
- o **Clean the AC filter** at least once a fortnight. A choked filter means a poorer quality of cooling and more power consumed.
- o Replace old regulators with electronic regulators to help reduce electricity consumption significantly
- Whenever existing AC units are replaced or new ones are to be purchased, BEE 3-star
 or 5-star rated machines should be purchased.
- o For lights, fans and other equipment, it is recommended to engage with a service provider rather than purchase individual lights and fans. An **AMC Contract** should be signed with the service provider with the clause on '**Performance Guarantee**' with a penalty/incentive clause for maintaining the System's output. This will result in bringing in accountability from Project Developer/ service provider.

Best Practices:

- o Consider **Using the AC optimally** for an hour or two less every day. An AC switched off for an hour can keep a 20 W tube light on for 100 hours!
- o Maintain the A/c Temperature around 24°C 25°C (human comfort level).
- Keep windows shut after switching off the AC to keep the room cool for some more time. You would be saving significantly on power consumption.
- o Switch off the PCs when not in use.
- o Switch off lights and fans when leaving a room.
- o The above points may also be displayed in important spaces such as classrooms, computer labs, staff rooms, etc.

4.5 Recommendations for Electrical system and Earthing

It is recommended, to install hour meter as a check on the usage time of each pump to calculate the energy consumption of the pump. It is used to track and record the elapsed running time of the motor during service.

| Sr. | Observations | Recommendations | Risk |
|-----|---|---|----------|
| No. | | | category |
| 1 | 04 Nos of Hotspot found in changeover switch and distribution boards. (upto 106.3 degree). | Need to be attended on priority by taking following actions: - 1. Tightening of connections. 2. Re-lugging of cable ends 3. Replacing the wire leads if required. | High |
| 2 | Earthing resistance value for DG sets body, DG neutral earth, Changeover panel earth is found very high i.e up to 84 ohm. | Earthing resistance value should be less than 1.0ohm, As Standard limits of earth pit resistance specified in Indian electricity Act 2003 is up to 1 ohm. | High |
| 3 | Leakage current through earthing for main building DG body found high i.e. 117mA. | Earth Leakage current should be less than 30.0mA. This may increase the chances of electrical shock. Suggest attending the same on priority. | Medium |
| 4 | Neutral to earth voltage for main building and extension building incomers, distribution boards, Switchboards is found very high i.e. (44.7V) than the standard limits. | Need to attend the same (it should be less than 2.0V as per standard engineering practices) | High |
| 5 | A lightning arrestor is not provided for CHM College Main Building and Extension Building. | It is suggested to install Early streamer emission (ESE) type lightning arrestor for the premises which is required as per IS IEC 62305. | Medium |
| 6 | A single line diagram for the Electrical distribution system is not available with CHM College. | SLD of power distribution needs to be prepared and displayed at prominent locations. | Medium |
| 7 | Gland plate opening holes are found in distribution panels. | Gland plate opening holes need to be sealed by using a rubber grommet to avoid the reptile's entry inside the panel. | Medium |

| 8 | Cable joint found in between MSEB meter to Main Outgoing MCCB of all the three sources. | Suggest replacing the cable to avoid cable joints. | Medium |
|----|--|--|---------|
| 9 | The insulated rubber mat is not provided in front of the main panel of the Main Building and extension building. | Insulated Rubber mat complying with IS 15652 should be provided in front of Electrical panels and distribution boards. | Low |
| 10 | Load found unbalanced for all three incoming sources. | Load need to be balanced. | Medium. |
| 11 | During socket testing, Earthing was found faulty for both the building and all floor sockets installed. | Wiring corrections of phase, neutral and earth need to be properly done. | Medium |
| 12 | Loose and hanging wires were found near floor distribution boards. | Earthing cables need to be terminated inside distribution boards. | Medium |
| 13 | A shock treatment chart is not provided near electrical panels which are required as per I.E. rules and are checked during a regular electrical inspection by electrical inspectors. | A shock treatment chart needs to be provided in the electrical panel areas. Suitable training needs to be provided to all the electrical working personnel on regular basis. | Low |
| 14 | A 52-week Preventive Maintenance schedule is not available for site equipment and electrical & fire system. | A preventive maintenance plan needs to be prepared to cover all the equipment covering AC, Electrical and fire systems installed at the site. | Medium |
| 15 | Lux level for Extension Building classrooms is found very low. | Suggested to replace Tubelights/ PL by LED Lights | Medium |

Table 31: Issues in electrical system w.r.t to their risk category and recommendation

4.6. Energy Bills

4.6.1. Change of Tariff

All the meters of the college are currently billed under LT II B i.e. commercial tariff is applicable. As college comes under the non-government institutional category, can apply and change their tariff to LT VII B. This tariff has fixed charges, costs that do not change with electricity usage. This amount is fixed in a customer's monthly bill. Whereas current demand charges are the costs that vary according to electricity usage. The more the electricity usage, the higher this portion of the bill. These are the costs other than, wheeling charge, per unit electricity charges etc. as shown in the table below.

| Tariff Category | Contract | Fixed Demand | Energy | Wheeling | Overall |
|-----------------|---------------|------------------|--------|----------|-----------|
| | Demand / | charge /Month | charge | charge | Cost per |
| | Load | | ₹/Unit | ₹/Unit | Unit |
| LT II B | >20 - ≤ 50 kW | Rs. 427 per kW | 10.79 | 1.35 | 18.48 |
| (Commercial) | | | | | |
| LT VII B | >20 - ≤ 50 kW | Rs.384.00 per kW | 7.23 | 1.35 | Around 14 |
| (Educational | | | | | |
| Institutional) | | | | | |

As per the current annual consumption of 95,498 units, the bill amount paid is Rs. 17,59,577/-. Assuming Rs 14/unit, this could have been reduced to 13,36,972/- making a saving of **Rs. 4,22,605/-**

4.6.2.Installation of APFC panel

Currently out of 3 metered connections, 2 bills have a provision of power factor incentive. As per the electricity bill shared the power factor is 0.97 and 0.99.

It is recommended to install Automatic power factor correction panel of 40KVAR capacity each and maintain the power factor up to 0.995 (unity) to get a maximum incentive of 3.5% of the monthly bill.

Additional incentive expected per annum will be **Rs.96,000/-** which will be recovered in approx. **1.5 years** considering the investment of around **1.5 Lacs**.

4.7 Retrofit of Water Efficient Equipment

Replacement with water-efficient equipment can lead to considerable water savings:







Plate 32: Proposed Dual Flush

Replacement with water-efficient equipment can lead to considerable water savings:



Plate 33: Proposed water-saving aerators for the wash basin faucets

| S. No. | Existing equipment | Replacement of existing equipment with energy-efficient equipment | No. of units | Current Water consumption (litres) | Projected Water savings with efficient equipment (litres) - Annual | Unit rate (Rs) | Total Cost (Rs) | Payback period (Year/ Months) |
|--------|--------------------------------|--|--------------|---|--|----------------------|-----------------------|--|
| 1 | Single Flush | Dual Flush | 24 | 120 | 72 | 3840 | 92160 | NA |
| 2 | Regular Washbasin faucet | Water-saving aerator faucet | 17 | 17 | 9 | 8.5 | 144.5 | NA |

Table 32: Retrofit for Water Efficient Equipment

A water meter should be installed to measure the water usage from the well. The water meter costs around Rs 500.

Use of Drip irrigation instead of manual using pipe to water trees and use of sprinkle for lawns can further help reduce water consumption for landscaping.

4.8 Waste Segregation and Composting

As college already has waste segregation in place, organic composting and maintenance and collection of recyclable waste can be undertaken by contract with NGO such as Stree Mukti Sanghatana, i.e resuming the service, which was suspended due to the pandemic. Incentive based collection campaigns should be organized under NSS/NCC program for collecting Multilayer plastic and tetra packs. This would create awareness amongst the faculty and students of the college, in the process reducing pollution and facilitating recycling of those.

4.9 Indoor Air Quality

Since the building is naturally ventilated, indoor air quality is not a major concern. Indoor plants can be added in administrative areas and hanging pots in corridors can be added to increase biodiversity and improve air quality can be provided in the administrative areas on all floors.







Plate 34: Indoor plants - Dieffenbachia amoena, Chlorophytum comosum and Epimnum auries

4.10 Environment Improvement

Plant and tree species that attract birds and butterflies can be planted to increase biodiversity of the campus. As the college has a lot of green space around, planting trees to the existing botanical and butterfly garden is recommended.



Plate 35: Plant species attracting birds and butterflies

Considering the universal access, the building should have a lift in the passage of Main building. This could facilitate the movement of special abled students and faculties on all the spaces of floors above ground.

4.11 Green Rating

The college can apply for following green building rating for evaluating performance and getting green rated:

| Sr. | Rating | Provided by | Performance | Registration / Rating fees |
|-----|---|--|--|---|
| No. | | | Evaluation | |
| 1. | EDGE | IFC, World Bank | Water, Waste and Energy | Pre-certification plus final EDGE certification – INR 1,20,000 + INR 9 per each additional sq m above 5,000 sq m. |
| 2. | IGBC – Existing buildings | CII, IGBC | Whole building | Registration fees – INR 25,000 and certification fees – INR 50,000 |
| 3. | BEE star rating | BEE, Govt. of India | Energy | Application to BEE |
| 4. | GRIHA – Existing buildings | Green Rating for Integrated Habitat Assessment (GRIHA) Council | Whole Building | INR 2,00,000 + INR 3.5 per additional sq. m over 5,000 sq. m |
| 5. | GEM Sustainability (Green) Certification Program - Campus (Educational/Corpo rate and Others) | ASSOCHAM Green & Eco- friendly Movement (GEM) | Site Area (Acres) - Less than 10 Acres | Pre-certification fee INR 1,75,000 + ASSOCHAM Certification fee INR 2,50,000 |

Table 33: Green Building Rating Systems

5. Glossary

- **Ballast:** A device used in conjunction with an electric-discharge lamp to cause the lamp to start and operate under proper circuit conditions of voltage, current, waveform, electrode heat, etc.
- **Built up area (BUA):** Sum of the covered areas of all floors of a building, other than the roof, and areas covered by external walls and parapet on these floors.
- **Common area:** Areas within a building that are available for use by all users in a building (i.e. lobbies, corridors, restrooms, etc.).
- **Connected load:** The sum of the rated wattage of all equipment, appliances and devices to be installed in the building or part of building or building complexes, in terms of kilowatt (kW) that will be allocated to all applicants for electric power consumption in respect of the proposed building or building complexes on their completion.
- **Contract demand:** The maximum demand in kilo Volt Ampere (kVA) (within a consumer's sanctioned load) agreed to be supplied by the electricity provider or utility in the agreement executed between the user and the utility or electricity provider.
- Colour Rendering Index (CRI): Colour Rendering Index (CRI) Measure of the
 degree to which the psychophysical colour of an object illuminated by the test
 illuminant conforms to that of the same object illuminated by the reference
 illuminant, suitable allowance having been made for the state of chromatic
 adaptation.
- **Correlated Colour Temperature (CCT) (K):** The temperature of the Planckian radiator whose perceived colour most closely resembles that of a given stimulus at the same brightness and under specified viewing conditions.
- **Demand:** Maximum rate of electricity (kW) consumption recorded for a building or facility during a selected time frame.
- **Demand factor**: Is the ratio of the sum of the maximum demand of a system (or part of a system) to the total connected load on the system (or part of the system) under consideration. Demand factor is always less than one.
- **Diversity factor**: The ratio between the actual power (Pact) and the rated power (P max) of systems.

- **Dry Bulb Temperature:** The temperature of the air, read on a thermometer, taken in such a way so as to avoid errors due to radiation.
- **Efficacy:** The lumens produced by a lamp plus ballast system divided by the total watts of input power (including the ballast), expressed in lumens per watt.
- **Energy:** Power derived from renewable or non-renewable resources to provide heating, cooling and light to a building or operate any building equipment and appliances. It has various forms such as thermal (heat), mechanical (work), electrical, and chemical that may be transformed from one into another. Customary unit of measurement is watts (W).
- Energy Conservation Building Code (ECBC): The Energy Conservation Building Code as updated from time to time by the Bureau and displayed on its website. (www.beeindia.gov.in).
- **Energy Efficiency Ratio (EER):** the ratio of net cooling capacity in watt to total rate of electric input in watts under design operating conditions.
- Energy Performance Index (EPI): of a building means its annual energy consumption in kilowatt-hours per square meter of the area of the building which shall be calculated in the existing or proposed building as per the formula annual energy consumption in kWh/total built-up area (excluding storage area and the parking in the basement) in m²
- **EPI Ratio:** of a building means the ratio of the EPI of the Proposed Building to the EPI of the Standard Building.
- **Equipment:** Mechanical, electrical or static devices for operating a building, including but not limited to those required for providing cooling, heating, ventilation, lighting, service hot water, vertical circulation.
- **Equipment, existing:** Equipment previously installed in an existing building.
- **Illuminance:** At a point on a surface, the ratio of the luminous flux incident on an infinitesimal element of the surface containing the point under consideration to the area of the element.
- **Interior Lighting Power**: LPD x Gross Lighted Floor Area.
- **Kilowatt (kW):** The basic unit of electric power, equal to 1000 W.
- **Lighting system:** A group of luminaires circuited or controlled to perform a specific function.

• Lighting power allowance:

- (a) Interior lighting power allowance: the maximum lighting power in watts allowed for the interior of a building
- (b) Exterior lighting power allowance: the maximum lighting power in watts allowed for the exterior of a building
- **Lighting Power Density:** Maximum lighting power per unit area of a space as per its function or building as per its classification.
- **Lumen (lm)**: SI unit of luminous flux. The luminous flux emitted within unit solid angle (one steradian) by a point source having a uniform intensity of one candela.
- **Luminaires:** A complete lighting unit consisting of a lamp or lamps together with the housing designed to distribute the light, position and protect the lamps, and connect the lamps to the power supply.
- Lux: The unit of illuminance (the measurement of illumination) is lux which is 1 lumen per m².
- National Building Code 2016 (NBC): model building code that provides guidelines for design and construction of buildings. In this code, National Building Code 2016 refers to the latest version by the Bureau of Indian Standards.
- **Reflectance:** The ratio of the light reflected by a surface to the light incident upon it.
- **Space:** An enclosed area within a building. The classifications of spaces are as follows for purpose of determining building envelope requirements:
 - (a) Conditioned space: a cooled space, heated space, or directly conditioned space.
 - (b) Semi-heated space: an enclosed space within a building that is heated by a heating system whose output capacity is greater or equal to 10.7 W/m2 but is not a conditioned space.
 - (c) Non-conditioned space: an enclosed space within a building that is not conditioned space or a semi-heated space. Crawlspaces, attics, and parking garages with natural or mechanical ventilation are not considered enclosed spaces.

- **Specific Energy Consumption:** The Specific Energy Consumption (SEC) is defined as the energy consumption per unit of product output.
- **Unconditioned buildings:** Building in which more than 90% of spaces are unconditioned spaces.
- **Unconditioned space:** Mechanically or naturally ventilated space that is not cooled or heated by mechanical equipment.
- **Uniformity Ratio:** Minimum illuminance divided by average illuminance levels.
- **Ventilation:** The process of supplying or removing air by natural or mechanical means to or from any space. Such air is not required to have been conditioned.
- **Watt:** The unit of power.
- **Wall Window Ratio:** The ratio of vertical fenestration area to gross exterior wall area. Gross exterior wall area is measured horizontally from the exterior surface; it is measured vertically from the top of the floor to the bottom of the roof.
- **Wet Bulb Temperature:** The steady temperature finally given by a thermometer having its bulb covered with gauze or muslin moistened with distilled water and placed in an air stream of not less than 4.5 m/s.
- **Working Plane:** A horizontal plane at a level at which work will normally be done.

6. References

- 1. Bluestone Hockley. (2015, October 9). QuickFacts: Transitioning from T12 to T8, T5 or LED Lighting for Commercial Buildings. Portland, Oregon, USA.
- 2. Bureau of Energy Efficiency. (2017). *Energy Conservation Building Code 2017.*Bureau of Energy Efficiency, Ministry of Power, Government of India. New Delhi: Bureau of Energy Efficiency.
- 3. Bureau of Energy Efficiency. (2011, January 22). *Energy Efficiency Benchmarks for Commercial Buildings in India.* Retrieved May 10, 2019, from Bureau of Energy Efficiency: www.beeindia.gov.in
- 4. Bureau of Energy Efficiency. (2009, March 25). *Energy Management in Your School.* Retrieved May 10, 2019, from Bureau of Energy Efficiency: www.beeindia.gov.in
- 5. Central Electricity Authority. (2014). *CO2 Baseline Database for the Indian Power Sector.* Ministry of Power, Government of India, Central Electricity Authority. New Delhi: Central Electricity Authority.
- 6. Deb, C., Lee, S., Yang, J., & Santamouris, M. (2015). Forecasting Energy Consumption of Institutional Buildings in Singapore. *Procedia Engineering*. Research Gate.
- 7. Dunselman, A. (2013). *Inside Innovation*. Retrieved May 10, 2019, from Phillips: www.phillips.com
- 8. Jain, A. (2018, June 25). Choose the right Regulator for Ceiling Fan for Electricity Saving. New Delhi, Delhi, India.
- 9. Pullen, S. (2000). Energy Assessment of Institutional Buildings. *Proceedings of the 34th Conference of the Australia and New Zealand Architectural Science Association* (pp. 47-52). ANZAScA.

7. Annexure


A. Usage data collection template

| Sr No | Name of the room | Name of the Space | Area | Floor | Maximum No. Of Persons at a time | Type of Light (LED/ Halogen/ Tubelight/ | LED/NON LED | Total no. | Approximate Wattage | Usage hours/day | Total no. of days used | Total usage Wh/year | Total usage KWh/year | Connected Load | LPD calculation | LPD | AC/ NON AC |
|-------|--------------------------------|-------------------|--------|--------------|-------------------------------------|--|-------------|-----------|------------------------|--------------------|------------------------|------------------------|-------------------------|----------------|-----------------|---------------|---------------|
| 1 | NSS Room | G-01 | 11.62 | Ground Floor | 8 | LED Tubelights | LED | 2 | 36 | | 300 | 172800 | 57.6 | 72 | 6.20 | Compliant | Non AC |
| 2 | NCC-Boys | G-02 | 11.62 | Ground Floor | 8 | LED Tubelights | LED | 2 | 36 | 8 | 300 | 172800 | 57.6 | 72 | 6.20 | Compliant | Non AC |
| 3 | NCC-Girls | G-03 | 11.62 | Ground Floor | 8 | LED Tubelights | LED | 3 | 36 | 8 | 300 | 259200 | 86.4 | 108 | 9.30 | Compliant | Non AC |
| 4 | First Aid | G-04 | 9.29 | Ground Floor | 2 | LED Tubelights | LED | 2 | 36 | 8 | 365 | 210240 | 70.08 | 72 | 7.75 | Compliant | Non AC |
| 5 | Examination Room-1 | G-05 | 12 | Ground Floor | 4 | LED Tubelights | LED | 3 | 36 | 8 | 60 | 51840 | 17.28 | 108 | 9.00 | Compliant | Non AC |
| 6 | Teachers common Room | G-06 | 55.2 | Ground Floor | 50 | LED Tubelights | LED | 14 | 36 | 8 | 245 | 987840 | 329.28 | 504 | 9.13 | Compliant | AC |
| 7 | Meeting room | G-07 | 16.56 | Ground Floor | | LED Tubelights | LED | 6 | 36 | 8 | 245 | 423360 | 141.12 | 216 | 13.04 | Non Compliant | Non AC |
| 8 | Chemistry Lab-1 PG | G-08 | 55.2 | Ground Floor | 25 | LED Tubelights | LED | 14 | 36 | 8 | 245 | 987840 | 329.28 | 504 | 9.13 | Compliant | Non AC |
| 9 | Enquiry | G-09 | 5.81 | Ground Floor | 4 | LED Tubelights | LED | 2 | 36 | 8 | 245 | 141120 | 47.04 | 72 | 12.40 | Non Compliant | Non AC |
| 10 | Library | G-10 | 82.8 | Ground Floor | 100 | LED Tubelights | LED | 69 | 36 | 8 | 300 | 5961600 | 1987.2 | 2484 | 30.00 | Non Compliant | Non AC |
| 11 | Online public access catalogue | G-11 | 82.8 | Ground Floor | 4 | LED Tubelights | LED | 2 | 36 | 8 | 300 | 172800 | 57.6 | 72 | 0.87 | Compliant | Non AC |
| 12 | Book Bank | G-12 | 82.8 | Ground Floor | 4 | LED BULBS | LED | 6 | 15 | 8 | 300 | 216000 | 72 | 90 | 1.09 | Compliant | Non AC |
| 13 | Chemistry Lab | G-13 | 36.8 | Ground Floor | 4 | LED BULBS | LED | 2 | 15 | 8 | 245 | 58800 | 19.6 | 30 | 0.72 | Compliant | Non AC |
| 14 | Chemistry Lab | G-14 | 55.2 | Ground Floor | 50 | LED BULBS | LED | 52 | 15 | 8 | 245 | 1528800 | 509.6 | 780 | 14.13 | Non Compliant | Non AC |
| 15 | Chemistry Lab | G-15 | 41.4 | Ground Floor | 20 | LED Tubelights | LED | 13 | 36 | 8 | 245 | 917280 | 305.76 | 468 | 11.30 | Non Compliant | Non AC |
| 16 | Chemistry Lab | G-16 | 36.8 | Ground Floor | 4 | LED Tubelights | LED | 2 | 36 | 8 | 245 | 141120 | 47.04 | 72 | 1.96 | Compliant | Non AC |
| 17 | Chemistry Lab | G-17 | 55.2 | Ground Floor | 50 | LED Tubelights | LED | 18 | 36 | 8 | 245 | 1270080 | 423.36 | 648 | 11.74 | Non Compliant | Non AC |
| 18 | Store Room | G-18 | 18.4 | Ground Floor | 2 | LED Tubelights | LED | 3 | 36 | 8 | 300 | 259200 | 86.4 | 108 | 5.87 | Compliant | Non AC |
| 19 | Gas Room | G-19 | 18.4 | Ground Floor | 2 | LED Tubelights | LED | 2 | 36 | 8 | 300 | 172800 | 57.6 | 72 | 3.91 | Compliant | Non AC |
| 20 | Store Room | G-20 | 18.4 | Ground Floor | 2 | LED Tubelights | LED | 2 | 36 | 5 | 50 | 18000 | 6 | 72 | 3.91 | Compliant | AC |
| 21 | Board Room | G-21 | 55.2 | Ground Floor | 25 | LED Tubelights | LED | 33 | 15 | 8 | 300 | 1188000 | 396 | 495 | 8.97 | Compliant | Non AC |
| 21 | Girls common Room | 101 | 55.74 | First Floor | 30 | LED Tubelights | LED | 10 | 36 | 8 | 245 | 705600 | 235.2 | 360 | 6.46 | Compliant | Non AC |
| 22 | Lecture Room 1 | 102 | 83.61 | First Floor | 100 | LED Tubelights | LED | 13 | 36 | 8 | 245 | 917280 | 305.76 | 468 | 5.60 | Compliant | Non AC |
| 23 | Lecture Room 2 | 103 | 55 | First Floor | 50 | LED Tubelights | LED | 9 | 36 | 8 | 245 | 635040 | 211.68 | 324 | 5.89 | Compliant | Non AC |
| 24 | Facilitation Room | 104 | 11.8 | First Floor | 5 | LED Tubelights | LED | 3 | 36 | 8 | 245 | 211680 | 70.56 | 108 | 9.15 | Compliant | Non AC |
| 25 | Admin Office | 105 | 111.5 | First Floor | 30 | LED BULBS | LED | 60 | 15 | 8 | 300 | 2160000 | 720 | 900 | 8.07 | Compliant | Non AC |
| 26 | Registrar Office | 106 | 12 | First Floor | 6 | LED tubelights | LED | 6 | 36 | 8 | 300 | 518400 | 172.8 | 216 | 18.00 | Non Compliant | Non AC |
| 27 | IT Lab 1 | 107 | 55.2 | First Floor | 50 | LED tubelights | LED | 10 | 36 | 8 | 245 | 705600 | 235.2 | 360 | 6.52 | Compliant | AC |
| 28 | Principal's office | 108 | 16.56 | First Floor | 10 | LED tubelights | LED | 14 | 36 | 8 | 300 | 1209600 | 403.2 | 504 | 30.43 | Non Compliant | AC |
| 29 | Vice Principal's office | 109 | 36.8 | First Floor | 10 | LED BULBS | LED | 47 | 15 | 8 | 300 | 1692000 | 564 | 705 | 19.16 | Non Compliant | AC |
| 30 | HOD Marathi | 110 | 8.9 | First Floor | 6 | LED tubelights | LED | 1 | 36 | | 245 | 70560 | 23.52 | 36 | 4.04 | Compliant | Non AC |
| 31 | HOD Economics | 111 | 8.9 | First Floor | 4 | LED tubelights | LED | 2 | 36 | | 245 | 141120 | 47.04 | 72 | 8.09 | Compliant | Non AC |
| 32 | Water Room | 112 | 8.9 | First Floor | 2 | LED tubelights | LED | 1 | 36 | | 365 | 105120 | 35.04 | 36 | 4.04 | Compliant | Non AC |
| 33 | Exam Room | 113 | 83.6 | First Floor | 10 | LED tubelights | LED | 8 | 36 | | 300 | 691200 | 230.4 | 288 | 3.44 | Compliant | Non AC |
| 34 | Exam Control Room | 114 | 2.78 | First Floor | 6 | LED tubelights | LED | 4 | 36 | | 120 | 138240 | 46.08 | 144 | 51.80 | Non Compliant | Non AC |
| 35 | Physics Lab | 115 | 139.35 | First Floor | 50 | LED tubelights | LED | 31 | 36 | | 245 | 2187360 | 729.12 | 1116 | 8.01 | Compliant | Non AC |
| 36 | IQAC Room | 116 | 27.9 | First Floor | 20 | LED tubelights | LED | 4 | 36 | | 300 | 345600 | 115.2 | 144 | 5.16 | Compliant | AC |
| 37 | , | 117 | 83.6 | First Floor | 50 | LED tubelights | LED | 11 | 36 | | 245 | 776160 | 258.72 | 396 | 4.74 | Compliant | Non AC |
| 38 | | 118 | 55.74 | First Floor | 4 | LED tubelights | LED | 2 | 36 | | 245 | 141120 | 47.04 | 72 | 1.29 | Compliant | Non AC |
| 39 | | 119 | 34.8 | First Floor | 50 | LED tubelights | LED | 18 | 36 | | 245 | 1270080 | 423.36 | 648 | 18.62 | Non Compliant | Non AC |
| 40 | IT Lab 2 | 120 | 27.9 | First Floor | 50 | LED tubelights | LED | 10 | 36 | | 245 | 705600 | 235.2 | 360 | 12.90 | Non Compliant | AC |
| 41 | HOD Sindhi | 121 | 8.9 | First Floor | 4 | LED tubelights | LED | 2 | 36 | | 245 | 141120 | 47.04 | 72 | 8.09 | Compliant | Non AC |
| 42 | Micro Biology Lab | 201, 202, | 205.5 | Second Floor | 60 | LED tubelights | LED | 24 | 36 | | 245 | 1693440 | 564.48 | 864 | 4.20 | Compliant | Non AC |
| 43 | HOD Microbiology | 204 | 11.8 | Second Floor | 6 | LED tubelights | LED | 2 | 36 | | 245 | 141120 | 47.04 | 72 | 6.10 | Compliant | Non AC |
| 44 | Zoology Lab | 205 | 83.6 | Second Floor | 6 | LED tubelights | LED | 12 | 36 | | 245 | 846720 | 282.24 | 432 | 5.17 | Compliant | Non AC |
| 45 | Preparation Room | 206 | 2.78 | Second Floor | 10 | LED tubelights | LED | 7 | 36 | 8 | 245 | 141120 | 47.04 | 72 | 25.90 | Non Compliant | Non AC |

| | Name of | | Maximum No. Of | Type of Fan (Ceiling/ Exhaust/ Wall | Total no. | Approximate | Usage Hours | Total no. of | Total usage | Total usage | Connected |
|-------|-----------|--------|-------------------|-------------------------------------|-----------|-------------|-------------|--------------|-------------|-------------|-----------|
| S. No | the Space | Floor | Persons at a time | Mounted Fan/ Pedestal Fan) | of Fans | Wattage | per day | days used | Wh/year | KWh/year | Load |
| 1 | G-01 | Ground | 8 | Ceiling Fans | 1 | 53 | 8 | 300 | 127200 | 42.40 | 53 |
| 2 | G-02 | Ground | 8 | Ceiling Fans | 1 | 53 | 8 | 300 | 127200 | 42.40 | 53 |
| 3 | G-03 | Ground | 8 | Ceiling Fans | 1 | 53 | 8 | 300 | 127200 | 42.40 | 53 |
| 4 | G-04 | Ground | 2 | Ceiling Fans | 1 | 53 | 8 | 365 | 154760 | 51.59 | 53 |
| 5 | G-05 | Ground | 4 | Ceiling Fans | 1 | 53 | 8 | 60 | 25440 | 8.48 | 53 |
| 6 | G-06 | Ground | 50 | Ceiling Fans | 6 | 53 | 8 | 245 | 623280 | 207.76 | 318 |
| 7 | G-07 | Ground | | Ceiling Fans | 2 | 53 | 8 | 245 | 207760 | 69.25 | 106 |
| 8 | G-08 | Ground | 25 | Ceiling Fans | 12 | 53 | 8 | 245 | 1246560 | 415.52 | 636 |
| 9 | G-09 | Ground | 4 | Ceiling Fans | 1 | 53 | 8 | 245 | 103880 | 34.63 | 53 |
| 10 | G-10 | Ground | 40 | Ceiling Fans | 37 | 53 | 8 | 300 | 4706400 | 1568.80 | 1961 |
| 11 | G-11 | Ground | 4 | Ceiling Fans | 1 | 53 | 8 | 300 | 127200 | 42.40 | 53 |
| 12 | G-12 | Ground | 4 | Ceiling Fans | 4 | 53 | 8 | 300 | 508800 | 169.60 | 212 |
| 13 | G-13 | Ground | 4 | Ceiling Fans | 1 | 53 | 8 | 245 | 103880 | 34.63 | 53 |
| 14 | G-14 | Ground | 50 | Ceiling Fans | 9 | 53 | 8 | 245 | 934920 | 311.64 | 477 |
| 15 | G-15 | Ground | 20 | Ceiling Fans | 6 | 53 | 8 | 245 | 623280 | 207.76 | 318 |
| 16 | G-16 | Ground | 4 | Ceiling Fans | 1 | 53 | 8 | 245 | 103880 | 34.63 | 53 |
| 17 | G-17 | Ground | 50 | Ceiling Fans | 7 | 53 | 8 | 245 | 727160 | 242.39 | 371 |
| 18 | G-18 | Ground | 2 | Ceiling Fans | 2 | 53 | 8 | 300 | 254400 | 84.80 | 106 |
| 19 | G-19 | Ground | 2 | Ceiling Fans | 5 | 53 | 8 | 300 | 636000 | 212.00 | 265 |
| 20 | G-20 | Ground | 25 | Ceiling Fans | 5 | 53 | 8 | 245 | 519400 | 173.13 | 265 |
| 21 | G-22 | Ground | 60 | Ceiling Fans | 8 | 53 | 8 | 245 | 831040 | 277.01 | 424 |
| 22 | G-23 | Ground | 30 | Ceiling Fans | 3 | 53 | 8 | 245 | 311640 | 103.88 | 159 |
| 23 | G-24 | Ground | 30 | Ceiling Fans | 3 | 53 | 8 | 245 | 311640 | 103.88 | 159 |
| 24 | G-25 | Ground | 30 | Ceiling Fans | 3 | 53 | 8 | 245 | 311640 | 103.88 | 159 |
| 25 | G-26 | Ground | 30 | Ceiling Fans | 5 | 53 | 8 | 245 | 519400 | 173.13 | 265 |
| 26 | G-27 | Ground | 30 | Ceiling Fans | 5 | 53 | 8 | 245 | 519400 | 173.13 | 265 |
| 27 | G-28 | Ground | 30 | Ceiling Fans | 5 | 53 | 8 | 245 | 519400 | 173.13 | 265 |
| 28 | G-29 | Ground | 30 | Ceiling Fans | 5 | 53 | 8 | 245 | 519400 | 173.13 | 265 |
| 29 | G-30 | Ground | 30 | Ceiling Fans | 4 | 53 | 8 | 245 | 415520 | 138.51 | 212 |
| 30 | 101 | First | 30 | Ceiling Fans | 6 | 53 | 8 | 245 | 623280 | 207.76 | 318 |
| 31 | 102 | First | 100 | Ceiling Fans | 9 | 53 | 8 | 245 | 934920 | 311.64 | 477 |
| 32 | 103 | First | 50 | Ceiling Fans | 6 | 53 | 8 | 245 | 623280 | 207.76 | 318 |
| 33 | 104 | First | 5 | Ceiling Fans | 1 | 53 | 8 | 245 | 103880 | 34.63 | 53 |
| 34 | 105 | First | 30 | Ceiling Fans | 17 | 53 | 8 | 300 | 2162400 | 720.80 | 901 |
| 35 | 106 | First | 6 | Ceiling Fans | 2 | 53 | 8 | 300 | 254400 | 84.80 | 106 |
| 36 | 107 | First | 50 | Ceiling Fans | 4 | 53 | 8 | 245 | 415520 | 138.51 | 212 |
| 37 | 108 | First | 10 | Ceiling Fans | 5 | 53 | 8 | 300 | 636000 | 212.00 | 265 |
| 38 | 109 | First | 10 | Ceiling Fans | 5 | 53 | 8 | 300 | 636000 | 212.00 | 265 |
| 39 | 110 | First | 6 | Ceiling Fans | 1 | 53 | 8 | 245 | 103880 | 34.62666667 | 53 |
| 40 | 111 | First | 4 | Ceiling Fans | 1 | 53 | 8 | 245 | 103880 | 34.62666667 | 53 |

| S. No | Name of the Space | Floor | Name of the Equipment | Total no. of Equipment | Approximate Wattage (W) | Usage hours/ day | Total no. of days used | Total usage Wh/year | Total usage KWh/year | Connected Load |
|-------|--|--------------|-----------------------|---------------------------|----------------------------|---------------------|------------------------|------------------------|-------------------------|-------------------|
| 1 | G-15 (Chemistry Analytical Lab.) | Ground Floor | spectrophotometer | 2 | 500 | 0 | 0 | 0 | 0 | 1000 |
| 2 | G-15 (Chemistry Analytical Lab.) | Ground Floor | Magnetic Stirrer | 1 | 300 | 1 | 90 | 27000 | 9.00 | 300 |
| 3 | G-15 (Chemistry Analytical Lab.) | Ground Floor | Colorimeter | 5 | 200 | 5 | 180 | 900000 | 300.00 | 1000 |
| 4 | G-15 (Chemistry Analytical Lab.) | Ground Floor | pH Meter | 6 | 100 | 5 | 180 | 540000 | 180.00 | 600 |
| 5 | G-17 (Chemistry Junior Lab.) | Ground Floor | Weighing Balance | 1 | 100 | 6 | 180 | 108000 | 36.00 | 100 |
| 6 | G-14 (Chemistry Senior Lab.) | Ground Floor | Oven | 1 | 1500 | 5 | 60 | 450000 | 150.00 | 1500 |
| 7 | G-14 (Chemistry Senior Lab.) | Ground Floor | Weighing Balance | 2 | 100 | 6 | 180 | 216000 | 72.00 | 200 |
| 8 | Office administration area | First Floor | Biometrics | 3 | 2 | 8 | 245 | 11760 | 3.92 | 6 |
| 9 | 107 (I.T. Lab. 1) | First Floor | Computer /Laptop | 26 | 100 | 6 | 180 | 2808000 | 936.00 | 2600 |
| 10 | 120 (I.T. Lab. 2) | First Floor | Computer /Laptop | 24 | 100 | 6 | 180 | 2592000 | 864.00 | 2400 |
| 11 | 115 (Physics Sr. Lab.) | First Floor | Computer /Laptop | 5 | 100 | 3 | 180 | 270000 | 90.00 | 500 |
| 12 | 115 (Physics Sr. Lab.) | First Floor | Printer | 1 | 30 | 1 | 180 | 5400 | 1.80 | 30 |
| 13 | 115 (Physics Sr. Lab.) | First Floor | Heating Coils | 2 | 1000 | 1 | 60 | 120000 | 40.00 | 2000 |
| 14 | 115 (Physics Sr. Lab.) | First Floor | CRO | 6 | 40 | 6 | 245 | 352800 | 117.60 | 240 |
| 15 | 115 (Physics Sr. Lab.) | First Floor | Weighing Balance | 1 | 100 | 1 | 60 | 6000 | 2.00 | 100 |
| 16 | 117 (Physical Chem. Lab.) | First Floor | Computer /Laptop | 1 | 100 | 1 | 245 | 24500 | 8.17 | 100 |
| 17 | 117 (Physical Chem. Lab.) | First Floor | Printer | 1 | 30 | 1 | 245 | 7350 | 2.45 | 30 |
| 18 | 117 (Physical Chem. Lab.) | First Floor | Water Bath | 3 | 1000 | 2 | 180 | 1080000 | 360.00 | 3000 |
| 19 | 119 (Physics Junior Lab.) | First Floor | Heating Coils | 3 | 1000 | 0.5 | 30 | 45000 | 15.00 | 3000 |
| 20 | 119 (Physics Junior Lab.) | First Floor | CRO | 1 | 40 | 3 | 90 | 10800 | 3.60 | 40 |
| 21 | 119 (Physics Junior Lab.) | First Floor | Weighing Balance | 1 | 100 | 3 | 30 | 9000 | 3.00 | 100 |
| 22 | 201, 202, 203 (Microbiology Laboratory | Second Floor | Fridge | 6 | 240 | 24 | 365 | 12614400 | 4204.80 | 1440 |
| 23 | 201, 202, 203 (Microbiology Laboratory | Second Floor | Oven | 4 | 1500 | 3 | 270 | 4860000 | 1620.00 | 6000 |
| 24 | 201, 202, 203 (Microbiology Laboratory | Second Floor | Computer /Laptop | 1 | 100 | 4 | 250 | 100000 | 33.33 | 100 |
| 25 | 201, 202, 203 (Microbiology Laboratory | Second Floor | Printer | 1 | 30 | 0.5 | 180 | 2700 | 0.90 | 30 |
| 26 | 201, 202, 203 (Microbiology Laboratory | Second Floor | Water Bath | 1 | 1500 | 0.5 | 30 | 22500 | 7.50 | 1500 |
| 27 | 201, 202, 203 (Microbiology Laboratory | Second Floor | Weighing Balance | 2 | 100 | 3 | 280 | 168000 | 56.00 | 200 |
| 28 | 201, 202, 203 (Microbiology Laboratory | Second Floor | Distillation Unit | 1 | 2000 | 0.5 | 280 | 280000 | 93.33 | 2000 |
| 29 | 201, 202, 203 (Microbiology Laboratory | Second Floor | Laminar | 1 | 450 | 0.5 | 50 | 11250 | 3.75 | 450 |
| 30 | | Second Floor | Spectrophotometer | 1 | 500 | 0.5 | 30 | 7500 | 2.50 | 500 |

B.Sample Floor Layouts








Figure 15: Campus Layout

C.Sample Electricity bill of Smt. Chandibai Himathmal Mansukhani college



D.Sample Water bill



E.Green census report

The objective of the green census is 1. To evaluate the present status of individual trees, and shrubs and to quantify the greenery found on campus 2. To label the trees and shrubs of the campus which will provide information about the scientific name, common name and vernacular name, and importance. 3. to educate the students and staff about the different tree species that they encounter in their daily lives. 4. To maintain an inventory of tree and shrub diversity, health status, frequency, and distribution to create a more reliable database of tree species.

Methodology - The project was be carried out in two phases by the staff and students of the Botany department. Mr. Prashant Patil, Dr. Lakshmi Girish, Dr. Neelam Parab led the project. The TY students were involved in the project. In the first phase, the students were divided into groups and they were taught about the identification and numbering system of the trees and shrubs. Each group was guided by project leaders of Botany Department. All the trees and shrubs having a height of 6 mts were considered for the census. Inside the garden, all trees, shrubs and herbs were recorded. The groups were allotted different locations on the campus to carry out the census. Finally, the individual data was compiled and the final report was prepared. During the census, the students recorded the health status of the trees. In the second phase of the project, with the prepared census data name plates were prepared using metal sheets. The trees were numbered and the nameplates were attached to them. The nameplate reveals the details about the tree such as botanical name, common name and family.

The campus was divided into five locations for the convenience of the project study. The following are the area covered during the census

- 1. From the college gate till the building entrance
- 2. Near the Pharmacy college building
- 3. Nearby and back of the canteen
- 4. Inside and surrounding the garden
- 5. The area behind the junior chemistry lab to the main entrance of the annexure building

The study recorded a total of 308 trees and shrubs species on the campus which count the number of trees and shrubs. There are 75 trees belonging to 26 different plant species recorded from the main gate to the entrance of the college.

List of plants from the college gate till the building entrance

| Sr. | Deterior nome | Common Nome | Family | No. of |
|-----|---------------------------------------|-----------------------------|----------------|--------|
| No. | Botanical name | Common Name | Family | Plants |
| 1 | Terminalia catappa L. | Indian Almond | Combretaceae | 04 |
| 2 | Terminalia tomentosa Wight & Arn | Crocodile Bark tree | Combretaceae | 01 |
| 3 | Samanea saman Merr. | The Rain Tree | Mimosae | 03 |
| 4 | Peltophorum pterocarpum Backer. | Copper Pod Tree | Caesalpinaceae | 04 |
| 5 | Cassia siamea Lamk. | Kassod | Caesalpinaceae | 02 |
| 6 | Pithocolobium dulce Benth. | Manila Tamarind | Mimosae | 04 |
| 7 | Spathodea campanulate <u>P.Beauv.</u> | African Tulip Tree | Bignoniaceae | 06 |
| 8 | Quisqualis indica L | Rangoon creeper | Combrtaceae | 02 |
| 9 | Ficus religiosa L. | Pipal | Moraceae | 01 |
| 10 | Ficus glomerata Roxb. | Umber | Moraceae | 01 |
| 11 | Caesalpinea pulcherrima Linn. | Peacock Flower | Caesalpinaceae | 10 |
| 12 | Azardirachta indica A. juss. | Margosa Tree | Meliaceae | 01 |
| 13 | Antigonon leptopus Hook. & Arn | Icecream creeper | Polygonaceae | 01 |
| 14 | Vernonia elaeagnifolia DC | Curtain plant | Asteraceae | 01 |
| 15 | Chrysalidocarpous lutescens H. Wendl. | Madagascar Palm. | Palmae | 04 |
| 16 | Annona squamosa L. | Custard Apple | Annonaceae. | 01 |
| 17 | Tecoma stans (L.) Juss. ex Kunth | Yellow bells | Bignoniaceae | 01 |
| 18 | Alstonia scholaris R. Br | Devil's tree, saptaparni | Apocynaceae | 01 |
| 19 | Morinda citrifolia L. | Indian Mulberry, Noni | Rubiaceae | 01 |

| 20 | Pongamia pinnata Pierre. | Pongam Tree, Karanj | Papilionaceae | 01 | |
|-------|--------------------------------|----------------------|---------------|----|--|
| 21 | Trema orientalis (L.) Bl. | pigeon wood | Ulmaceae | 01 | |
| 22 | Ficus benjamina L. | Weeping fig | Moraceae | 01 | |
| 23 | Pedilanthus thithimaloides | Ladies slipper plant | Euphorbiaceae | 05 | |
| 24 | Casuarina equisitifolia | | Amentiferae | 01 | |
| 25 | Prosopis cineraria; (L.) Druce | Khejri Tree | Mimosae | 01 | |
| 26 | Bamboosa arundinaceae | Bamboo | | 15 | |
| Total | | | | | |

The area in front of the pharmacy college consist of total 18 trees and shrubs belonging to 11 different plant species.

List of plants near the Pharmacy college building

| | | | Total | 18 |
|-----|--|----------------------|----------------|--------|
| 11 | Cassia fistula L. | Golden shower | Caesalpinaceae | 01 |
| 10 | Grevillea robusta; A.Cunn. ex R.Br. | Silver Oak | | 01 |
| 9 | Peltophorum pterocarpum Backer. | Copper Pod Tree | Caesalpinaceae | 01 |
| 8 | Ficus benjamina L. | Weeping fig | Moraceae | 01 |
| 7 | Pongamia pinnata Pierre. | Karanj | Papilionaceae | 01 |
| 6 | Ficus glomerata Roxb. | Umber | Moraceae | 02 |
| 5 | Ficus religiosa L. | Pipal | Moraceae | 01 |
| 4 | Roystonea regia (Kunth) O.F. Cook | Royal palm | Palmae | 04 |
| 3 | Spathodea campanulate <u>P.Beauv.</u> | African Tulip Tree. | Bignoniaceae | 02 |
| 2 | Butea monosperma (Lam.)Taub. | Flame of the Forest, | Papilionaceae | 01 |
| 1 | Polyalthia longifolia (Sonn.) Thwaites | False Ashoka | Annonaceae | 03 |
| No. | | | | Plants |
| Sr. | Botanical name | Common Name | Family | No. of |

The area Nearby and back of the canteen consist of total 13 huge trees and shrubs belonging to 8 different plant species.

Nearby and back of the canteen

| Sr. | Botanical name | Common Name | Family | No. of |
|-----|---------------------------------|-----------------|----------------|--------|
| No. | | | | Plants |
| 1 | Samanea saman Merr. | The Rain Tree | Mimosae | 04 |
| 2 | Psidium guajava L. | Guava | Myrtaceae | 01 |
| 3 | Ficus religiosa L. | Pipal | Moraceae | 01 |
| 4 | Ficus benghalensis L. | Banyan tree | Moraceae | 01 |
| 5 | Acacia auriculiformis Benth. | | Mimosae | 01 |
| 6 | Pongamia pinnata Pierre. | Karanj | Papilionaceae | 03 |
| 7 | Peltophorum pterocarpum Backer. | Copper Pod Tree | Caesalpinaceae | 01 |
| 8 | Trema orientalis (L.) Bl. | pigeon wood | Ulmaceae | 01 |
| | | • | Total | 13 |

The botanical garden (K. M. Kundnani Botanical Garden) was recorded to be the most rich and diverse location in the campus. The interiors and surrounding the garden consist of in total 158 trees and shrubs belonging to 54 different plant species.

Inside and surrounding the garden

| Sr.No. | Botanical name | Common Name | Family | No. of |
|--------|---------------------------------------|------------------|----------------|--------|
| | | | | Plants |
| 1 | Anacardium occidentale L. | Cashew nut | Anacardiaceae | 02 |
| 2 | Psidium guajava L. | Guava | Myrtaceae | 01 |
| 3 | Ficus religiosa L. | Pipal | Moraceae | 01 |
| 4 | Cycas circinalis | The queen sago | Cycadaceae | 02 |
| 5 | Ecbolium viride (Forssk.) Alston | Blue fox tail | Acanthaceae | 10 |
| 6 | Pongamia pinnata Pierre. | Karanj | Papilionaceae | 03 |
| 7 | Peltophorum pterocarpum Backer. | Copper Pod Tree | Caesalpinaceae | 01 |
| 8 | Ficus benjamina | Weeping fig | Moraceae | 01 |
| 9 | Chrysalidocarpous lutescens H. Wendl. | Madagascar Palm. | Palmae | 10 |

| 10 | Polyalthia longifolia (Sonn.) Thwaites | False Ashoka | Annonaceae | 15 |
|----|--|------------------------------|----------------|----|
| 11 | Cocos nucifera L. | Coconut palm | Palmae | 20 |
| 12 | Auracaria auracana | monkey puzzle tree | Auracariaceae | 01 |
| 13 | Azadirachta indica A. Juss | Margosa Tree | Meliaceae | 02 |
| 14 | Agalonema commutatum Schott. | Chinese evergreen | Araceae | 02 |
| 15 | Kopsia fruticosa (Roxb.) A. DC. | Pink kopsia | Apocynaceae | 01 |
| 16 | Cassia fistula L. | Indian laburnum | Caesalpinaceae | 03 |
| 17 | Carissa carandus | Karanda | Apocynaceae | 02 |
| 18 | Livistona chinensis · (Jacq.) R.Br. ex Mart. | Chinese Fan palm | Palmae | 01 |
| 19 | Roystonea regia (Kunth) O.F. Cook | Royal palm | Palmae | 01 |
| 20 | Madhuca indica | honey tree | Sapotaceae | 01 |
| 21 | Plumbago zeylanica L. | Ceylon leadwort | Plumbaginacae | 10 |
| 22 | Aegle marmelos (L.) Correa | Wood apple | Rutaceae | 07 |
| 23 | Murraya koenigii (L.) Spreng | Curry leaf tree | Rutaceae | 08 |
| 24 | Phyllanthus reticulatus Poir | Black-berried Featherfoil | Euphorbiaceae | 01 |
| 25 | Nephrolepis exapltata | sword fern | Polypodiaceae | 03 |
| 26 | Fargesia rufa | Bamboo grass | Graminae | 01 |
| 27 | Achras sapota L. | Sapota | Sapotaceae | 01 |
| 28 | Murraya paniculata · (L.) Jack | China-box | Rutaceae | 01 |
| 29 | Syzygium jambolanum (Lam.) DC. | Java plum | Myrtaceae | 04 |
| 30 | Dieffenbachia seguine (<u>Jacq.</u>) <u>Schott</u> | Dumbane | Araceae | 09 |
| 31 | Gliricidia sepium (Jacq.) Steud. | Mexican Lilac | Papilionaceae | 01 |
| 32 | Schefflera arboricola (Hayata) Merr | Umbrella plant | Araliaceae | 02 |
| 33 | Baliospermum montanum (Willd.) Müll.Arg. | Red Physic Nut, | Euphorbiaceae | 01 |
| 34 | Curcuma longa L. | Turmeric | Zingiberaceae | 03 |
| 35 | Clerodendrum inerme (L.) Gaertn. | the glory bower | Papilionaceae | 01 |
| 36 | Butea monosperma (Lam.)Taub. | Flame of the Forest, | Papilionaceae | 01 |
| 37 | Mangifera indica L. | Mango tree | Anacardiaceae | 03 |
| 38 | Morus alba L. | White Mulberry | Moraceae | 01 |
| 39 | Annona squamosa L. | Custard apple | Annonaceae | 01 |

| 40 | Polyscias scutellaria | Sheild Aralia | Araliaceae | 01 |
|----|---|-----------------------------|----------------|-----|
| 41 | Areca catechu L. | Betel nut Palm | Palmae | 01 |
| 42 | Thespesia populnea (L.) Soland. ex Correa | Portia Tree | Malvaceae | 01 |
| 43 | Delonix regia (Hook.) Raf | May flower | Caesalpinaceae | 01 |
| 44 | Asparagus racemosus Willd | Shatavari | Liliaceae | 01 |
| 45 | Pavetta indica L. | Bride's bush | Rubiaceae | 01 |
| 46 | Pandanus odoratissimus L.f. | Screw pine | Pandanaceae | 01 |
| 47 | Citrus limon (L.) Burm.f. | Lemon | Rutaceae | 01 |
| 48 | Pimenta Dioica [(L) Merr. | All spice or Jamaica pepper | Myrtaceae | 01 |
| 49 | Ficus glomerata Roxb. | Cluster fig | Moraceae | 01 |
| 50 | Adhatoda vasica (L.) Nees | Malabar nut | Acanthaceae | 01 |
| 51 | Terminalia catappa L. | Indian almond | Combretaceae | 01 |
| 52 | Monstera deliciosa Liebm. | Split leaf philodendron | Araceae | 01 |
| 53 | Canna indica L. | Edible canna | Cannaceae | 01 |
| 54 | Bauhinia purpurea L | Purple bauhinia | Caesalpinaceae | 05 |
| | | Total | | 158 |

The area behind the junior chemistry lab to the main entrance of the annexure building consists of a total of 44 trees and shrubs belonging to 17 different plant species.

Area behind the junior chemistry lab till the main entrance of annexure building

| Sr. No. | Botanical name | Common Name | Family | No. of Plants |
|------------|-----------------------------------|---------------|----------------|---------------|
| 1 | Terminalia catappa L. | Indian almond | Combretaceae | 04 |
| 2 | Cocos nucifera L. | Coconut palm | Palmae | 05 |
| 3 | Ficus religiosa L. | Pipal | Moraceae | 04 |
| 4 | Roystonea regia (Kunth) O.F. Cook | Royal palm | Palmae | 01 |
| 5 | Achras sapota L. | Sapota | Sapotaceae | 01 |
| 6 | Ficus benjamina | Weeping fig | Moraceae | 04 |
| 7 | Mangifera indica L. | Mango tree | Anacardiaceae | 04 |
| 8 | Psidium guajava L. | Guava | Myrtaceae | 01 |
| 9 | Tamarindus indica L. | Tamarind | Caesalpinaceae | 01 |

| 10 | Luecana leucocephala | Babool | Mimosae | 01 | |
|----|--|--------------------------|---------------|----|----|
| 11 | Alstonia scholaris R. Br | Devil's tree, saptaparni | Apocynaceae | 01 | |
| 12 | Hibiscus rosa-sinensis L. | Shoe flower | Malvaceae | 01 | |
| 13 | Acalypha wilkesiana Muell. Arg | Copperleaf | Euphorbiaceae | 01 | |
| 14 | Gardenia jasminoides J. Ellis. | Cape Jasmine | Rubiaceae | 02 | |
| 15 | Dieffenbachia seguine (<u>Jacq.</u>) <u>Schott</u> | Dumbane | Araceae | 07 | |
| 16 | Lagerstroemia flos-reginae Retz. | Pride of India, | Lythraceae | 01 | |
| 17 | Ixora coccinea L. | Scarlet jungle flame | Rubiaceae | 05 | |
| | | • | Total | | 44 |

The green census revealed the fact that the campus is very rich in its vegetation especially the biodiversity of tree species. The prominent trees which were recorded were *Polyalthia*, *Peltophorum*, *Samanea*, *Spathodea and Terminalia* etc. while among the shrubs *Chrysalidocarpus*, *Ixora*, *Diffenbeckia etc* were recorded. *Samanea and Peltophorum* trees were of over 70 years old trees of the campus which reflects the history and glory of the college.

The campus has proud of having many medicinal and ornamental plants. The small herbaceous plants were not taken into consideration because of their annual nature of growth. There are several trees with edible fruits, including Jamun, Guava, cashew nut, mulberry, anjeer, chikoo and mango. The large canopy with spreading branched trees support a rich avian diversity also. Most of the trees recorded on the campus were of indigenous origin which gives stability to the ecosystem. The large trees with huge canopy and branches make the atmosphere pure and oxygen-rich. The presence of large open spaces and the deep root system of the trees helps the campus to recharge a huge amount of rainwater which will help to support the neighbouring population. During the study, some of the trees were found to be infected and dead which were removed then after so that other tree species could be well protected.

Dr. Lakshmi Girish (Incharge of green Census)

Mr. Prashant Patil, (HOD, Botany)


Dr. Neelam Parab (Senior Staff, Junior college)


F. Certificates and bills of waste disposal.


a. Green certificate





b. Bills of paper trash.












G. Energy benchmarks for Commercial Buildings



Based on the data collected from different categories of commercial buildings, the following tables show the indicative EPI benchmarks.

EPI benchmarks for Office Buildings

| Climate Zone | Less than 50% AC | More than 50% AC |
|-----------------|---------------------|---------------------|
| EPI (kWh/m²/yr) | | |
| Warm & Humid | 101 | 182 |
| Composite | 86 | 179 |
| Hot & Dry | 90 | 173 |
| Moderate | 94 | 179 |

EPI benchmarks for Shopping Malls

| Climate Zone | EPI (kWh/m²/yr) |
|--------------|-----------------|
| Warm & Humid | 428 |
| Composite | 327 |
| Hot & Dry | 273 |
| Moderate | 257 |
| - | 273 |

EPI benchmarks for Hospitals

| Climate Zone | EPI (kWh/m²/yr) |
|--------------|-----------------|
| Warm & Humid | 275 |
| Composite | 264 |
| Hot & Dry | 261 |
| Moderate | 247 |

EPI benchmarks for Hotels

| Climate Zone | Upto 3 star | Above 3 star |
|-----------------|-------------|--------------|
| EPI (kWh/m²/yr) | | |
| Warm & Humid | 215 | 333 |
| Composite | 201 | 290 |
| Hot & Dry | 167 | 250 |
| Moderate | 107 | 313 |

EPI benchmarks for Institutes

| Climate Zone | EPI (kWh/m²/yr) |
|--------------|-----------------|
| Warm & Humid | 150 |
| Composite | 117 |
| Hot & Dry | 106 |
| Moderate | 129 |

EPI benchmarks for BPOs

| Climate Zone | EPI (kWh/m²/yr) |
|--------------|-----------------|
| Warm & Humid | 452 |
| Composite | 437 |
| Hot & Dry | - |
| Moderate | 433 |

Disclaimer: The EPI benchmarks should be considered as an Indicative figure as it largely depends upon the operating hours, energy efficiency measures, sample size, climatic zone and lack of detailed information by building owners.







Bureau of Energy Efficiency 4th Floor, Sewa Bhawan, R.K. Puram, New Delhi – 110066

Website: www.beenet.in

H.List of Vendors

Solid Waste Management

Ms. Jyoti Mhapsekar,

President,

Stree Mukti Sanghatana (SMS) Mobile: +91 9867724529

Chembur Center

Room No. 14 Santiniketan Chawl, Postal colony, Next to BD Shukla school Chembur, Mumbai - 400071

Phone: 022 65745837/022 25274588

Email: smspv123@gmail.com

Govandi Office

Ahilyabai Holkar Marg, Near Jafri High School bus stop,

Govandi- Mumbai - 400043 Phone: 022 65745840

Email: smspbvs@gmail.com

Solar PV panels

Avesta Solar

Dossabhoy Manison A, Ground floor plot no. 796, Jame Jamshed Road, Dadar East, Mumbai - 400014

Phone: 09819867196

IOT based monitoring

Ecolibrium Energy

IOT powered Asset Intelligence Software

Contact: Bhavesh Bhatt Mobile: 9833821814

Email: bhavesh.bhatt@ecolibrium energy.com

I. Unitary AC Operation, Inspection and Maintenance Guidelines

INSTALLATION

- 1. Outdoor Unit of Split Unit should be located such that it has free flow of air for heat rejection
- 2. Safety protocol to be followed as per the OEM guidelines
- 3. Earthing to be properly provided to the Unit
- 4. Checking the Voltage Supply levels (Phase to Neutral 230 Volts, Phase to Earth 230 Volts, Neutral to Earth \leq 0.5 -1 Volts
- 5. Electrical Compartment should be properly closed to avoid water ingress at the Electrical connections at the Outdoor Unit
- 6. Indoor Unit to be located to ensure free flow of air and proper circulation for effective cooling
- 7. Condensate Water Drain from Indoor Unit to be properly provided with adequate slope for water to drain off by gravity
- 8. Water drain to have proper Water Seal to avoid foul smell entering the conditioned space
- 9. Proper Insulation of Refregerant Lines (To & From Indoor & Out door Unit) to be provided.
- 10. Insulation material's protection by Tape or Aluminium thin foil is highly desirable for longevity of Insulation
- 11. Window AC's Condenser should be installed such that it has free flow of air for heat rejection
- 12. Ensure Proper Sealing of Conditioned spaces @ Window Sills, Glass Panes etc.
- 13. Double Glazed Units (DGU) are highly desirable for Windows. If not posssible to changeover, Install Heat resistant Films on the Existing Glass panes.
- 14. Roofing material should exhibit Good Thermal Resistance proprerties. (Insulation to be provided at the Roof)
- 15. Heat Gain through Glazing and Roof can have significant contribution towards

Energy Consumption of the AC.

OPERATIONS

- 1. Every 1° C lowering of Room Temperature set point, results in 3-5% increase in Energy Consumption
- 2. Ideal Room Temperature Set point @ 25° C
- 3. Energy savings can be achieved by Increasing Set point to 26° C and operate Ceiling Fan at lower Speed.
- 4. Ceiling Fans to be of BLDC (Brushless Direct Current) technology with offers @ 50% energy saving as compared to Conventional Fans.
- 5. Install 'Energy Saver' having features viz. 'High Accuracy Thermostat' (± 1° C) control and Artificial Intelligent Microprocessor Controller.
- 6. Incase of multiple Units (Split/Window) in the premise, there are New Technological innovations on Demand Side controls resulting in Energy Savings.
- 7. Filters: Clean Filters has potential of Energy Savings @ 5%
- 8. Covid situation warrants great care on Filter cleanliness management.
- 9. Filters offering microscopic filteration properties are also available, proper evaluation to be done for a retrofit job.

INSPECTIONS

- **1. Condenser Coil** (Outdoor Unit of Split AC / Window AC external facing portion)
- a. Check the condition of Coils at regular intervals. It should be clear of 'fouling materials' eg. Dust, dirt, leaves etc.
- b. Ideal Frequency of Checking should be Monthly. It may be decided upon depending on the Location and weather conditions
- **2. Evaporator Coils** (Indoor Unit of Split AC / Window AC internal facing portion)
- a. Check the condition of Coils at regular intervals. It should be clear of 'fouling materials' eg. Dust, dirt, leaves etc.
- b. Ideal Frequency of Checking should be Quarterly. It may be decided upon depending on the Location and weather conditions

3. Filters @ Evarporator Coils

- a. Frequency of Check: Monthly or depending on the Usage and location
- b. Dry / Wet cleaning has to be determined as per the site condition requirement
- c. Replace the Filters as per OEM's guidelines
- d. Never operate the AC without Filter

4. Fan Motor

- a. Frequency of Check: Quaterly / Six monthly depending on the Usage.
- b. Check for Freeness of the Fan
- c. Clean the Dust accumulated on the Fan Blades
- d. Check for Vibration & Noise level
- e. Fan Mounting bracket's condition
- f. Wiring and Termination at the Motor

5. Compressor

- a. Frequency of Check: Quaterly / Six monthly depending on the Usage.
- b. Check for Vibration and Noise level
- c. Check for Wires & its Terminal point
- d. Check for Capacitor Condition. (If found bulging on sides or Top, replace it immedeately. Capacitors have been source of fire in ACs)
- e. Check for cleaninliness @ surrounding area

6. Refrigerant & Refrigerant Piping

- a. Frequency of Check: Annual
- b. Check for Refrigerant Piping Condition
- c. Harnessing of the Piping
- d. Insulation over the Piping Condition

7. Drain Pan

- a. Frequency of Check: Monthly / Quaterly depending on the Usage.
- b. Drain Pan should be clear of Water accumulation
- c. Check the outflow water point @ drain pan for clogging.

d. Outflow Pipe from the Drain to be properly in place.

8. Performance Check

- a. After Regular Checks / Servicing monitor the following
- i. Grill Temperature
- ii. Time required to attain the Temperature Set point
- iii. Start / Stop of Compressor w.r.t the Set Point
- iv. Current / Power drawn by the Fan Motor
- v. Current / Power drawn during starting of the Compressor and steady state operation

MAINTENANCE

- 1. SAFETY FIRST: SWITCH OFF THE POWER to the Unit, Lock Out & Tag Out (LOTO) the Supply Point to the Unit
- 2. Servicing to be done by Authorised Personnel
- 3. Post Maintenance the Unit needs to be Operated for One cooling cycle to demonstrate its performance
- 4. Proper Records with Historical Information on Faults attended, Parts replaced, Checks Performed etc.

J. Energy Auditor's Certificate

Regn. No. EA-4593



No. 1765

National Productivity Council

(National Certifying Agency)

PROVISIONAL CERTIFICATE

This is to certify that Mr. / Ms. Shripad Vishnu Kale

son | daughter of Mr./Ms. Vishnu Krishna Kale

has passed the National Certification Examination for Energy Auditors held in 2006, conducted on behalf of the Bureau of Energy Efficiency, Ministry of Power, Government of Energy Energy

He / She is qualified as Certified Energy Manager as well as Certified Energy Auditor.

He | She shall be entitled to practice as Energy Auditor under the Energy Conservation Act 2001, subject to the fulfillment of qualifications for the Accredited Energy Auditor and issue of certificate of Accreditation by the Bureau of Energy Efficiency under the said Act.

This certificate is valid till the issuance of an official certificate by the Bureau of Energy Efficiency.


Place : Chennai, India

Date: 2nd November, 2006

Il girchidamhan

Controller of Examination

K. BEE Master Trainer Certificate



L. BEE Empaneled Expert professional



ऊर्जा दक्षता ब्यूरो (भारत सरकार, विद्युत मंत्रालय)



BUREAU OF ENERGY EFFICIENCY

SERVE IT (Government of India, Ministry of Power) F.No.09/06/07/IMPL/ECBC | 1774 C NSERVE IT

28th March, 2016

Ms. Roshni Udyavar Yehuda Rachana Sansad's Institute of Environmental Architecture 278, Shankar Ghanekar Marg, Prabhadevi Mumbai - 400 025

Sub: Energy Conservation Building Code - Shortlisting of Architects/ Consultant

Dear Madam,

This has reference to your application for shortlisting of Architects/Consultants for implementing the Energy Conservation Building Code (ECBC). We are pleased to inform you that you have been shortlisted to act as the resource person of the Bureau of Energy Efficiency (BEE) for helping in building technical capacity and develop compliance procedures and tools for the effective implementation of the ECBC. In addition, you would also be expected to advise design professionals in modifying the standard specifications so as to correspond with the Code requirements.

We would like you to send in your acceptance to being associated with the BEE in providing technical assistance to all those seeking to adopt Energy Conservation Building Code

Yours faithfully,

(\$anjay Seth) Energy Economist

रवहित एवं राष्ट्रहित में ऊर्जा बचाएँ Save Energy for Benefit of Self and Nation

चौथा तल, सेवा भवन, आर० के० पुरम, नई दिल्ली-110 066 वेबसाईट/Website : www.beeinda.in 4th Floor, Sewa Bhawan, R.K. Puram, New Delhi-110 066 टेली/Tel.: 26179699 (5 Lines) फैक्स/Fax वि (11) 26178352

M. Renewable Energy Mashav Course Certificate

